

County Surveyor's Record, Douglas County, Oregon

17279

Dependent Resurvey, Portion of West Boundary,
T. 30 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

from which the original bearing trees

- A fir, 25 ins. diam., bears N. 42° E., 112 lks. dist., with healed blaze.
- A fir, 42 ins. diam., bears S. 66° E., 48 lks. dist., with healed blaze. (Record, 45 lks.)
- A fir, 33 ins. diam., bears S. 32° W., 27 lks. dist., with healed double blaze.
- A fir, 53 ins. diam., bears N. 15° W., 122 lks. dist., with healed blaze.

and bearing trees mkd. by Tracy


- A fir, 15 ins. diam., bears N. 35 1/2° E., 15 1/2 lks. dist., with healed double blaze.
- A yew, 10 ins. diam., bears S. 42 1/2° E., 46 lks. dist., with scribe marks S30 CS BT visible on partially healed blaze.
- A grand fir, 13 ins. diam., bears N. 39 1/4° W., 49 lks. dist., with illegible scribe marks visible on partially healed blaze.

The corner is located in NE. corner of logged area.

N. 0° 05' W., bet. secs. 19 and 24, marking and blazing the true line.

Ascend 10 ft. over SW. slope, through heavy timber and dense undergrowth.

- 0.70 Spur, slopes W.; desc. 100 ft. over NW. slope.
- 15.60 Boulder Creek, 30 lks. wide, course N. 60° W.; asc. 50 ft. over SW. slope.
- 19.40 Gravelled road, 30 lks. wide, course N. 80° W.; and S. 80° E.
- 20.03 Point for the S 1/16 sec. cor. of secs. 19 and 24.
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

- A fir, 8 ins. diam., bears N. 49° E., 67 lks. dist., mkd. S 1/16 S19 BT.
- A fir, 12 ins. diam., bears N. 76 1/2° W., 21 lks. dist., mkd. S 1/16 S24 BT.

Ascend 115 ft. over SW. slope.

- 26.95 Spur, slopes S. 25° E.; asc. 45 ft. over SE. slope.
- 31.90 Creek, 1 lk. wide, course S. 55° E.; asc. 130 ft. over SW. slope.