

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of West Boundary,
T. 30 S., R. 8 W., Willamette Meridian, Oregon 17280

CHAINS

40.06

Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original cor,

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 30 S
R 9 W R 8 W
1/4
S 24 | S 19
1980

from which

A fir, 13 ins. diam., bears S. 28° E., 7 1/2 lks. dist., mkd. 1/4 S19 BT.

A fir, 13 ins. diam., bears N. 56 1/2° W., 24 lks. dist., mkd. 1/4 S24 BT.

Ascend 370 ft. over SW. slope.

58.55

Ridge, bears N. 65° W. and S. 65° E.; desc. 105 ft. over NW. slope.

71.75

Gravelled road, 30 lks. wide, bears N. 50° W. and S. 50° E.

74.80

Spur, slopes N. 50° W.; desc. 65 ft. over NE. slope.

80.12

The cor. of secs. 13, 18, 19, and 24, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1964, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S
S 13 | S 18
S 24 | S 19
R 9 W R 8 W
1964

from which an original bearing tree

A fir, 48 ins. diam., bears N. 35° E., 60 lks. dist., no marks visible.

and bearing trees mkd. by Tracy

A fir, 13 ins. diam., bears N. 85° E., 13 lks. dist., with healed double blaze.

A fir, 15 ins. diam., bears S. 20° E., 40 lks. dist., with healed double blaze.

A fir, 9 ins. diam., bears S. 55° W., 19 lks. dist., with healed double blaze.

A fir, 12 ins. diam., bears N. 41 3/4° W., 15 lks. dist., with healed double blaze.