

County Surveyor's Record, Douglas County, Oregon

17281

Dependent Resurvey, Portion of West Boundary,
T. 30 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

Land, mountainous.
Soil, rocky clay.
Timber, fir, yew, hemlock, maple, madrone, willow, cedar,
and oak; undergrowth, blackberry, arrowwood, hazel,
Oregon grape, huckleberry, wild currant, fern, vine
maple, and young timber.

Dependent Resurvey of a
Portion of the Subdivisional Lines,
T. 30 S., R. 8 W., Willamette Meridian, Oregon

(Restoring the survey
by William H. Byars, U.S. Deputy Surveyor, in 1882)

From the 1/4 sec. cor. of secs. 19 and 30, perpetuated and
recorded by John M. Powell, Deputy County Surveyor, in
1967, monumented with an iron post, 1 1/4 ins. diam., firmly
set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S R 8 W
1/4 $\frac{S 19}{S 30}$
1967

from which the remains of an original bearing tree

A root hole, bears S. 15° W., 26 lks. dist.,
with a down hemlock alongside, 10 ins. diam.,
with scribe marks BT visible on partially
open blaze.

and bearing trees mkd. by Powell

A fir, 33 ins. diam., bears N. 28° E., 31 lks.
dist., with healed blaze.

A yew, 12 ins. diam., bears S. 67° W., 30 lks.
dist., with scribe marks 1/4 S30 BT visible on
open blaze.

S. 88° 44' W., bet. secs. 19 and 30, marking and blazing
the true line.

Descend 5 ft. over W. slope, through heavy timber and
dense undergrowth.

0.25 Creek, 10 lks. wide, course N.; asc. 220 ft. over NE.
slope.

9.50 Spur, slopes NW.; desc. 130 ft. over NW. slope.

17.45 Point for the W 1/16 sec. cor. of secs. 19 and 30.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in
the ground, with brass cap mkd.

W 1/16 $\frac{S 19}{S 30}$

1980

from which