

County Surveyor's Record, Douglas County, Oregon

17283

Subdivision of Section 19,
T. 30 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

T 30 S R 8 W
C 1/4 S 19

1980

from which

A fir, 6 ins. diam., bears S. 27 1/2° E., 11 1/2 lks. dist., mkd. C 1/4 S19 BT.

A fir, 6 ins. diam., bears N. 25 1/2° W., 6 lks. dist., mkd. C 1/4 S19 BT.

Ascend 310 ft. over broken S. slope.

58.10 Ridge, bears N. 60° E. and S. 60° W.; desc. 10 ft. over N. slope.

72.75 Dirt road, 30 lks. wide, bears E. and W.

73.00 Ridge, bears E. and W.; desc. 85 ft. over N. slope.

80.00 The 1/4 sec. cor. of secs. 18 and 19, monumented with the original corner tree, a cedar, 45 ins. diam., with axe marks visible on N. face, from which the remains of the original bearing trees

A fir, 45 ins. diam., bears N. 20° W., 45 lks. dist., with axe marks visible on bark blaze. (Record, N. 26° W., 43 lks.)

A root hole, bears S. 44° E., 27 lks. dist., with a down cedar alongside, 26 ins. diam., with healed blaze. (Record. S. 40° E.)

and the remains of bearing trees and a reference monument mkd. by Vernon R. Tracy, Deputy County Surveyor, in 1965

A fir, 9 ins. diam., bears N. 6° E., 38 lks. dist., with scribe marks WC 1/4 S18 CS BT visible on open blaze.

A sawed hemlock stump, 13 ins. diam., bears S. 29° E., 34 lks. dist., with scribe marks BT visible on open blaze.

An iron post, 1 1/4 ins. diam., bears East, 15 lks. dist., firmly set, projecting 10 ins. above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T30S R8W 1/4 S18 19 WC 10 FT W TO COR 1965.

No suitable trees available within limits in sec. 19.

From the 1/4 sec. cor. of secs. 19 and 20, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 30 S R 8 W
 1/4
S 19 | S 20
 1972

from which bearing trees mkd. by Akin