

County Surveyor's Record, Douglas County, Oregon

17284

Subdivision of Section 19,
T. 30 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 13 ins. diam., bears S. 75° E., 49 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears West, 42 lks. dist., with illegible scribe marks visible on partially healed blaze. (Record, 45 lks.)

S. 88° 53' W., on the E. and W. center line of sec. 19.

Ascend 40 ft. over NE. slope, through heavy timber and dense undergrowth.

2.30 Spur, slopes S. 20° E.; desc. 30 ft. over SW. slope.

5.10 Bottom of descent, slopes S.; asc. 75 ft. over SE. slope.

12.05 Spur, slopes S. 10° E.; desc. 20 ft. over SW. slope.

13.90 Head of ravine, drains S.; asc. 10 ft. over SE. slope.

17.20 Spur, slopes S.; desc. 185 ft. over SW. slope.

26.85 Creek, 3 lks. wide, course S. 35° W.; asc. 155 ft. over SE. slope.

37.65 Spur, slopes S.; desc. 40 ft. over SW. slope.


39.70 The center 1/4 sec. cor. of sec. 19.

Descend 90 ft. over SW. slope.

54.55 Creek, 3 lks. wide, course S. 10° W.; asc. 15 ft. over SE. slope.

57.16 Point for the center W 1/16 sec. cor. of sec. 19.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



from which

A fir, 13 ins. diam., bears N. 24 1/2° W., 10 1/2 lks. dist., mkd. C-W 1/16 S19 BT.

A fir, 13 ins. diam., bears S. 7 1/2° E., 13 lks. dist., mkd. C-W 1/16 S19 BT.

Ascend 40 ft. over SE. slope.

63.40 Spur, slopes S.; desc. 85 ft. over SW. slope.

81.61 The 1/4 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp.

From the S 1/16 sec. cor. of secs. 19 and 20, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

