

County Surveyor's Record, Douglas County, Oregon

17285

Subdivision of Section 19,
T. 30 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which the remains of bearing trees mkd. by Akin</p> <p style="padding-left: 40px;">A root hole, bears N. 32 1/2° E., 24 1/2 lks. dist., with a down fir alongside, 9 ins. diam., with scribe marks S 1/16 S20 BT visible on open blaze.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 56 1/2° W., 67 1/2 lks. dist., with fragmentary scribe marks visible on partially open balze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 8° E., 43 lks. dist., mkd. S 1/16 S20 BT.</p> <p>From this point, United States Coast and Geodetic Survey triangulation station "LIVE OAK 1942", bears S. 84° 25' E., 247.76 chs. dist., monumented with a concrete post, 10 ins. square, firmly set, projecting 8 ins. above ground, with a standard brass tablet, 3 1/2 ins. diam., set in top, mkd. LIVE OAK 1942 and a triangle.</p> <p>S. 88° 43' W., on the E. and W. center line of the SE 1/4 of sec. 19.</p> <p>Descend 20 ft. over SW. slope.</p>
20.75	<p>Creek, 4 lks. wide, course S. 10° E.; asc. 45 ft. over SE. slope.</p>
39.59	<p>The center S 1/16 sec. cor. of sec. 19.</p>
	<p>From the W 1/16 sec. cor. of secs. 19 and 30.</p> <p>N. 0° 24' W., on the N. and S. center line of the SW 1/4 of sec. 19.</p> <p>Descend 145 ft. over broken NW. slope.</p>
9.00	<p>Boulder Creek, 30 lks. wide, course N. 75° W.; asc. 100 ft. over SE. slope.</p>
14.10	<p>Gravelled road, 30 lks. wide, bears N. 85° E. and S. 85° W.</p>
20.00	<p>Point for the SW 1/16 sec. cor. of sec. 19, at intersection with the E. and W. center line of the SW 1/4 of sec. 19.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S 19</p> <p style="text-align: center;">1980</p>
	<p>from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 88° E., 7 1/2 lks. dist., mkd. SW 1/16 S19 BT.</p> <p style="padding-left: 40px;">A grand fir, 15 ins. diam., bears S. 55° W., 15 1/2 lks. dist., mkd. SW 1/16 S19 BT.</p> <p>Ascend 280 ft. over broken SE. slope, changing to SW. slope.</p>
40.00	<p>The center W 1/16 sec. cor. of sec. 19.</p>