

# County Surveyor's Record, Douglas County, Oregon

17289

Dependent Resurvey, Portion of N. Bdy.,  
T. 31 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

recorded by Floyd C. Frear, Deputy County Surveyors, in 1921, from original evidence no longer in existence, subsequently perpetuated and recorded by George J. Wenderoth, Deputy County Surveyor, in 1946, and James W. Byron, Deputy County Surveyor, in 1964, monumented with a sawed and decayed fir stump, 24 ins. diam., no marks visible, with an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above ground, alongside, from which the remains of the bearing trees mkd. by Cain

A root hole, bears N. 72° E., 30 lks. dist., with a down oak alongside, 26 ins. diam., with axe marks visible.

A root hole, bears S. 3 1/2° E., 79 lks. dist., with a down oak alongside, 18 ins. diam., with axe marks visible on decayed blaze.

and the remains of bearing trees mkd. by Wenderoth

A cedar, 17 ins. diam., bears S. 44° W., 41 lks. dist., with obliterated blaze.

A sawed fir stump, 18 ins. diam., bears N. 37° W., 19 lks. dist., with axe marks visible on bark.

and the bearing tree mkd. by Byron

A fir, 18 ins. diam., bears N. 33° W., 28 lks. dist., with obliterated blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in ground, in center of stump, with brass cap mkd.

T 30 S R 6 W  
1/4  $\frac{S\ 36}{S\ 1}$

T 31 S R 6 W  
1983

from which new bearing trees

A fir, 5 ins. diam., bears N. 24° E., 24 lks. dist., mkd. 1/4 S36 BT.

A fir, 21 ins. diam., bears S. 35 1/2° W., 40 1/2 lks. dist., mkd. 1/4 S1 BT.

From this corner, a point established by Gary Langlitz, Deputy County Surveyor, in 1979, bears S. 42° 14' E., 0.24 chs. dist., monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. DOUGLAS COUNTY SURVEYORS OFFICE T30S R6W 1/4 S36 S1 T31S 1979, from which bearing trees mkd. by Langlitz

A fir, 12 ins. diam., bears N. 40° E., 49 lks. dist., with scribe marks 1/4 S36 CS BT visible on open double blaze.

A fir, 18 ins. diam., bears S. 9 1/2° E., 52 lks. dist., with scribe marks 1/4 S1 CS BT visible on open double blaze.