

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of N. Bdy.,
T. 31 S., R. 6 W., Willamette Meridian, Oregon

17290

CHAINS

A fir, 16 ins. diam., bears S. 89° W., 40 lks. dist., with scribe marks 1/4 S1 CS BT visible on open double blaze.

A madrone, 10 ins. diam., bears N. 67 1/2° W., 69 lks. dist., with scribe marks 1/4 S36 CS BT visible on open blaze.

The corner is located in a woven wire fence, extending N. and E.

N. 89° 24' W., bet. secs. 1 and 36, marking and blazing the true line.

Descend 45 ft. over NW. slope, through heavy timber and dense undergrowth.

2.05 Ravine, drains N. 30° W.; asc. 25 ft. over NE. slope.

3.25 Spur, slopes N. 20° E.; desc. 70 ft. over NW. slope.

6.20 Shoestring Creek, 5 lks. wide, course N. 5° E.; asc. 190 ft. over SE. slope.

17.20 Spur, slopes N. 20° E.; asc. 5 ft. over NE. slope.

20.16 Point for the W 1/16 sec. cor. of secs. 1 and 36.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 $\frac{S\ 36}{S\ 1}$

1981

from which

A fir, 10 ins. diam., bears N. 45° E., 49 lks. dist., mkd. W 1/16 S36 BT.

An oak, 8 ins. diam., bears S. 55 1/2° E., 54 lks. dist., mkd. W 1/16 S1 BT.

Ascend 5 ft. over NE. slope.

20.85 Spur, slopes N. 5° E.; desc. 185 ft. over broken NW. slope.

33.30 Gravelled driveway, 20 lks. wide, bears N. and S.

33.45 Power line, bears N. 25° W. and S. 25° E.

37.65 Spur, slopes N. 65° E.; desc. 15 ft. over NW. slope.

39.35 Ravine, drains N. 60° E.; asc. 15 ft. over SE. slope.

40.32 The cor. of secs. 1, 2, 35, and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 30 S R 6 W

S 35 | S 36

S 2 | S 1

T 31 S

1969