

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **17292**
T. 31 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

N. 0° 13' E., bet. secs. 1 and 2.

Descend 490 ft. over broken NE. slope, through heavy timber and dense undergrowth.

19.95

The N 1/16 sec. cor. of secs. 1 and 2, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.

N 1/16
S 2 | S 1
1969

from which bearing trees mkd. by Roseberry and Garrison

A fir, 37 ins. diam., bears N. 47 1/2° E., 24 lks. dist., with healed blaze. (Record, N. 53° E.)

A fir, 33 ins. diam., bears S. 41° W., 21 lks. dist., with healed blaze.

N. 0° 18' E., beginning a new measurement.

Descend 50 ft. over NE. slope.

1.35

Creek, 1 lk. wide, course E.; asc. 5 ft. over SE. slope.

3.55

Spur, slopes N. 70° E.; desc. 100 ft. over NE. slope.

7.75

Ravine, drains E.; asc. 10 ft. over SW. slope.

11.15

Spur, slopes N. 60° E.; desc. 220 ft. over NW. slope.

20.80

Ravine, drains N. 50° E.; asc. 5 ft. over SE. slope.

21.40

The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, yew, oak, madrone, ash, hemlock, pine, and alder; undergrowth, poison oak, vine maple, Oregon grape, ferns, salal, arrowwood, hazel, manzanita, and young timber.

From the cor. of secs. 22, 23, 26, and 27, perpetuated by J. W. Cole, Deputy County Surveyor, in 1924, and by John M. Powell, Deputy County Surveyor, in 1966, as described in Douglas County Surveyor's Records, monumented with an iron bar, 1 in. square, firmly set, projecting 8 ins. above ground, with an iron post, 1 1/4 ins. diam., firmly set alongside, projecting 13 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 31 S R 6 W
S 22 | S 23

S 27 | S 26
1966