

County Surveyor's Record, Douglas County, Oregon

17293

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

from which the remaining original bearing trees

A madrone, 17 ins. diam., bears N. 52° E., 25 lks. dist., with illegible scribe marks visible on partially healed blaze.

A madrone, 12 ins. diam., bears S. 20° E., 28 lks. dist., with illegible scribe marks visible on partially healed blaze. (Record, 31 lks.)

A madrone, 8 ins. diam., bears N. 60° W., 55 lks. dist., with healed blaze.

and bearing trees marked by Cole in 1924

A fir, 28 ins. diam., bears S. 76 1/2° W., 118 lks. dist., with healed blaze.

A fir, 40 ins. diam., bears N. 45° W., 88 lks. dist., with healed blaze.

A fir, 18 ins. diam., bears N. 59 1/2° W., 104 lks. dist., with healed blaze.

and bearing trees marked by Powell in 1966

A fir, 28 ins. diam., bears S. 3° E., 37 lks. dist., with healed blaze.

A fir, 6 ins. diam., bears S. 53° W., 22 lks. dist., with healed blaze.

A fir, 11 ins. diam., bears N. 20° W., 23 lks. dist., with healed blaze.

N. 0° 08' W., bet. secs. 22 and 23.

Descend 155 ft. over NW. slope, through heavy timber and dense undergrowth.

9.95 Creek, 10 lks. wide, course N. 70° W.; asc. 105 ft. over SW. slope.

13.60 Spur, slopes S. 80° W.; desc. 50 ft. over NW. slope.

15.70 Creek, 2 lks. wide, course S. 70° W.; asc. 315 ft. over SW. slope.


37.90 Ridge, bears N. 75° W. and S. 60° E.; desc. 30 ft. over broken NE. slope.

39.20 Silver Butte Lookout road, gravelled, 25 lks. wide, bears N. 20° W. and S. 20° E.

40.84 Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 31 S R 6 W



Book 4/95
 BY LANG M 125-3