

County Surveyor's Record, Douglas County, Oregon

17294

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

from which

A fir, 6 ins. diam., bears S. 88° E., 40 lks.
dist., mkd. 1/4 S23 BT.

A fir, 10 ins. diam., bears N. 55 1/2° W., 67 lks.
dist., mkd. 1/4 S22 BT.


From this point, United States Geological Survey
triangulation station SILVER BUTTE Reference Mark No. 2,
bears S. 62° 25' E., 41.41 chs. dist., monumented with a
brass cap, 3 ins. diam., set in a concrete footing, 3 x 3
x 3 ft. square, at the southwest corner of lookout tower,
with brass cap mkd. SILVER BUTTE No. 2 1942 with an arrow
pointing to the corner. The triangulation station has
been removed or destroyed.

Descend 40 ft. over broken NE. slope.

51.05

Point for the S-N 1/64 sec. cor. of secs. 22 and 23.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in
the ground, with brass cap mkd.



from which

A fir, 6 ins. diam., bears S. 69 1/2° E., 72 lks.
dist., mkd. S-N 1/64 S23 BT.

A fir, 21 ins. diam., bears S. 75° W., 67 lks.
dist., mkd. S-N 1/64 S22 BT.

Descend 215 ft. over broken NE. slope.

58.00

Ravine, drains N. 70° E.; asc. 25 ft. over SE. slope.


60.10

Spur, slopes N. 85° E.; desc. 40 ft. over NE. slope.

61.26

Point for the N 1/16 sec. cor. of secs. 22 and 23.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in
the ground, with brass cap mkd.



from which

A fir, 14 ins. diam., bears N. 26 3/4° E., 5 lks.
dist., mkd. N 1/16 S23 BT.

A fir, 18 ins. diam., bears S. 73 3/4° W., 52 lks.
dist., mkd. N 1/16 S22 BT.

Descend 75 ft. over NE. slope.

63.95

Ravine, drains N. 85° E.; asc. 45 ft. over SE. slope.

73.10

Spur, slopes N. 85° E.; desc. 110 ft. over NE. slope.