

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, 17296
T. 31 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

A fir stump, 14 ins. diam., bears N. 30° W.,
32 lks. dist., with scribe mark B visible
on opened blaze on log lying alongside.
(Record, 30 lks.)

and bearing trees marked by Powell

A fir, 10 ins. diam., bears S. 37° E., 68 lks.
dist., with healed blaze.

A fir, 26 ins. diam., bears S. 8° W., 60 lks.
dist., with healed blaze.

A fir, 24 ins. diam., bears N. 51° W., 97 lks.
dist., with healed blaze.


N. 4° 24' W., bet. secs. 10 and 11.

Ascend 120 ft. over SE. slope, through heavy timber and
dense undergrowth.

20.07

Point for the S 1/16 sec. cor. of secs. 10 and 11.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in
the ground, with brass cap mkd.



from which

A madrone, 31 ins. diam., bears N. 32 1/2° E., 20 lks.
dist., mkd. S 1/16 S11 BT.

A fir, 15 ins. diam., bears S. 11° W., 23 lks.
dist., mkd. S 1/16 S10 BT.

Ascend 5 ft. over SE. slope.

26.50

Ridge, bears N. 60° E., S. 10° W., and N. 30° W.; desc.
305 ft. over NE. slope.


34.45

Gravelled road, 30 lks. wide, bears N. 75° W. and
S. 40° E.

40.14

The 1/4 sec. cor. of secs. 10 and 11, perpetuated by John
M. Powell, Deputy County Surveyor, in 1966, as described
in a Douglas County Surveyor's Record, monumented with an
iron post, 1 1/4 ins. diam., firmly set, projecting 16 ins.
above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE



from which the remains of an original bearing tree

A fir stump, 10 ins. diam., bears N. 60° W., 23 lks.
dist., with scribe marks BT visible on opened
blaze.