

County Surveyor's Record, Douglas County, Oregon

17297

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

and new bearing trees

A fir stump, 26 ins. diam., bears S. 8° E., 16 lks.
dist., mkd. 1/4 S11 BT.

A fir, 12 ins. diam., bears N. 19° W., 85 lks.
dist., mkd. 1/4 S10 BT.

The cor. is located in a clear cut. No other suitable
trees available within limits.

Land, mountainous.


Soil, rocky clay.

Timber, cedar, pine, fir, hemlock, yew, oak, maple, and
madrone; undergrowth, poison oak, arrowwood, hazel,
Oregon grape, manzanita, rhododendron, huckleberry,
blackberry, thimbleberry, salmonberry, ferns, salal, and
young timber.

From the cor. of secs. 21, 22, 27, and 28, perpetuated by
Vernon R. Tracy, Deputy County Surveyor, in 1964, as
described in a Douglas County Surveyor's Record,
monumented with an iron post, 1 1/4 ins. diam., firmly set,
projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 31 S R 6 W



1964

from which the remaining original bearing tree

A cedar, 32 ins. diam., bears N. 44° W., 48 lks.
dist., no scribe marks visible on opened blaze.

and the remains of bearing trees mkd. by Tracy

A fir, 16 ins. diam., bears S. 70° W., 26 lks.
dist., with a healed blaze.

A grand fir snag, 16 ins. diam., bears N. 15° W.,
45 1/2 lks. dist., with scribe marks T31S R6W S21
CS BT visible on open blaze.

and new bearing trees

A fir, 18 ins. diam., bears N. 37° E., 61 lks.
dist., mkd. T31S R6W S22 BT.

A fir, 30 ins. diam., bears S. 1 1/2° E., 103 lks.
dist., mkd. T31S R6W S27 BT.

N. 0° 14' E., bet. secs. 21 and 22.

Descend 25 ft. over NW. slope, through heavy timber and
dense undergrowth.

4.15 Creek, 20 lks. wide, course S. 75° W., asc. 80 ft. over
SE. slope.

14.75 Gravelled road, 30 lks. wide, bears S. 45° W. and
S. 45° E., in curve.