

County Surveyor's Record, Douglas County, Oregon

17299

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir root crown, bears N. 36° E., 16 lks. dist., with a down fir alongside, 8 ins. diam., with scribe marks T31S R6W S15 visible on opened blaze.</p> <p>A fir snag, 48 ins. diam., bears S. 35° E., 67 lks. dist., with no scribe marks visible on opened blaze.</p> <p>A fir snag, 30 ins. diam., bears N. 57° W., 21 lks. dist., with no scribe marks visible on opened blaze.</p> <p>and the remains of bearing trees and a reference monument mkd. by Tracy</p> <p>A root hole, bears S. 45° E., 17 lks. dist., with down fir alongside, 6 ins. diam., with scribe marks S15 visible on partially healed blaze.</p> <p>A fir, 10 ins. diam., bears S. 19 1/4° W., 37 lks. dist., with healed blaze.</p> <p>An iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above the ground, bears West, 6 lks. dist., with brass cap mkd. COUNTY SURVEYORS OFFICE WC 4 ft. E. T31S R6W S15 S16 S21 S22 1964.</p> <p>A root hole, bears N. 42° W., 8 lks. dist., with down fir alongside, 3 ins. diam., with scribe marks S 15 visible on open blaze.</p> <p>and bearing trees mkd. by Shaner</p> <p>A fir, 10 ins. diam., bears N. 9 3/4° E., 25 lks. dist., with scribe marks T31S R6W WC S15 BT visible on open blaze.</p> <p>A fir, 8 ins. diam., bears S. 20 1/4° E., 12 lks. dist., with scribe marks T31S R6W WC S22 BT visible on open blaze.</p> <p>A fir, 10 ins. diam., bears N. 71° W., 11 lks. dist., with scribe marks T31S R6W WC S16 BT visible on open blaze.</p> <p>The cor. lies 60 ft. E. of a ridge and a gravelled road, 30 lks. wide, both bear S. 20° E. and N. 20° W.</p> <p>Land, mountainous. Soil, rocky clay. Timber, willow, oak, madrone, ash, pine, fir, cedar, yew, alder, hemlock, and maple; undergrowth, rhododendron, fern, hazel, arrowwood, poison oak, manzanita, salal, Oregon grape, salmonberry, and huckleberry.</p>
	<p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>N. 89° 33' W., bet. secs. 10 and 15.</p> <p>Ascend 120 ft. over SE. slope, through heavy timber and dense undergrowth.</p>
4.00	Ridge, bears N. 25° E. and S. 25° W.; desc. 270 ft. over broken SW. slope.
6.10	Gravelled road, 40 lks. wide, bears N. 30° E. and S. 35° W.; enter clear-cut, edge bears same.