

County Surveyor's Record, Douglas County, Oregon

17301

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

A fir, 4 ins. diam., bears S. 36° E., 20 lks. dist., mkd. W 1/16 S15 BT.


A fir, 5 ins. diam., bears N. 51° W., 37 1/2 lks. dist., mkd. W 1/16 S10 BT.

Descend 725 ft. over NW. slope.

79.85 Creek, 10 lks. wide, course N. 10° W.; asc. 5 ft. over NE. slope.

80.04 The cor. of secs. 9, 10, 15, and 16, perpetuated by John M. Powell, Deputy County Surveyor, in 1970, as described in a Douglas County Surveyor's Record, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE



1970

from which the remains of an original bearing tree

A root hole, bears N. 73° W., 32 lks. dist., with down yew alongside, 12 ins. diam., with scribe mark 3 visible on decayed blaze.

and the remains of bearing trees mkd. by Powell

An alder, 9 ins. diam., bears N. 83 3/4° E., 16 lks. dist., with healed blaze.

A fir, 51 ins. diam., bears S. 13 1/2° E., 143 lks. dist., with illegible scribe marks visible on partially healed blaze.

A fir stump, 40 ins. diam., bears S. 64 1/4° W., 14 lks. dist., with scribe marks T31S R6W S16 BT visible on bark.

A yew, 20 ins. diam., bears N. 16 1/4° W., 89 lks. dist., with scribe marks T31S R6W S9 CS BT visible on open blaze.

and a new bearing tree

A fir, 5 ins. diam., bears S. 55° W., 42 lks. dist., mkd. T31S R6W S16 BT.

Land, mountainous.
Soil, rocky clay.
Timber, fir, yew, alder, maple, oak, cedar, hemlock, ash, willow, and madrone; undergrowth, poison oak, ferns, Oregon grape, rhododendron, manzanita, hazel, arrowwood, salal, huckleberry, salmonberry, blackberry, and young timber.

N. 0° 41' W., bet. secs. 9 and 10.

Descend 45 ft. over NE. slope, through heavy timber and dense undergrowth.