

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, 17302
T. 31 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
8.70	Creek, 7 lks. wide, course N. 30° W.; asc. 225 ft. over SW. slope.
19.99	Point for the S 1/16 sec. cor. of secs. 9 and 10. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> S 1/16 S 9 S 10 1980 </div> from which <div style="margin-left: 40px;"> A madrone, 24 ins. diam., bears S. 40° E., 15 lks. dist., mkd. S 1/16 S10 BT. A fir, 8 ins. diam., bears N. 50° W., 49 lks. dist., mkd. S 1/16 S9 BT. </div> Ascend 5 ft. over SW. slope.
20.55	Spur, slopes N. 50° W.; desc. 100 ft. over NW. slope.
22.95	Ravine, drains N. 80° W.; asc. 65 ft. over SW. slope.
28.30	Spur, slopes N. 55° W.; desc. 160 ft. over N. slope.
32.50	Ravine, drains N. 80° W.; asc. 165 ft. over S. slope.
39.98	Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 31 S R 6 W 1/4 S 9 S 10 1980 </div> from which <div style="margin-left: 40px;"> A fir, 5 ins. diam., bears S. 54 1/2° E., 45 lks. dist., mkd. 1/4 S10 BT. A fir, 8 ins. diam., bears S. 17° W., 24 lks. dist., mkd. 1/4 S9 BT. </div> Ascend 15 ft. over S. slope.
41.15	Spur, slopes N. 55° W.; desc. 320 ft. over NW. slope.
49.05	Creek, 10 lks. wide, course S. 80° W.; asc. 205 ft. over SW. slope.
52.75	Dirt road, 15 lks. wide, bears N. 70° E. and S. 70° W.
56.25	Spur, slopes N. 45° W.; desc. 20 ft. over NW. slope.
59.97	Point for the N 1/16 sec. cor. of secs. 9 and 10.