

County Surveyor's Record, Douglas County, Oregon

17303 Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

N 1/16
S 9 | S 10
1980

from which

A fir, 12 ins. diam., bears S. 30 3/4° E.,
13 1/2 lks. dist., mkd. N 1/16 S10 BT.

A fir, 10 ins. diam., bears N. 47° W.,
10 lks. dist., mkd. N 1/16 S9 BT.

Descend 150 ft. over NW. slope.

71.25 Ravine, drains N. 70° W.; asc. 90 ft. over SW. slope.

73.25 Spur, slopes W.; desc. 110 ft. over NW. slope.

77.80 Ravine, drains N. 85° W.; asc. 5 ft. over SW. slope.

79.96 The cor. of secs. 3, 4, 9, and 10, perpetuated by James W. Byron, Deputy County Surveyor, in 1960, as described in a Douglas County Surveyor's Record, monumented with the original cor. tree, a fir, 26 ins. diam., with illegible scribe marks visible on bark blaze, from which the remaining original bearing trees

A fir, 21 ins. diam., bears N. 28° E., 9 lks. dist., with illegible scribe marks visible on bark.

A fir, 27 ins. diam., bears S. 80° E., 25 lks. dist., with healed blaze.

A fir, 27 ins. diam., bears S. 31° W., 15 lks. dist., no marks visible. (Record, S. 25° W.)

and a bearing tree and witness monument by Byron

An iron post, 1 1/4 ins. diam., firmly set, projecting 16 ins. above the ground, with brass cap mkd.
COUNTY SURVEYORS OFFICE T31S R6W WC W 4.3 FT TO
COR, S3, S4, S9, S10, 1960 bears West, 7 lks. dist.

A fir, 18 ins. diam., bears N. 5° W., 72 lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, madrone, hemlock, pine, ash, alder, cedar, and yew; undergrowth, poison oak, fern, arrowwood, hazel, Oregon grape, salal, wild rose, vine maple, blackberry, rhododendron, manzanita, and young timber.

From the cor. of secs. 9, 10, 15, and 16.

N. 88° 23' W., bet. secs. 9 and 16.

Ascend 565 ft. over NE. slope, through heavy timber and dense undergrowth.