

County Surveyor's Record, Douglas County, Oregon

17304

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

- 17.10 Ridge, bears N. 35° E. and S. 30° W.; desc. 265 ft. over NW. slope.
- 25.10 Creek, 5 lks. wide, course N. 10° E.; asc. 185 ft. over E. slope.
- 31.35 Spur, slopes N. 30° E.; desc. 150 ft. over NW. slope.
- 40.00 The 1/4 sec. cor. of secs. 9 and 16, reestablished by proportionate measurement by Bruce A. Shaner, Registered Land Surveyor, No. 430, Oregon, in 1980, as described in a Douglas County Surveyor's Record, and accepted as the best available evidence of the position of the original cor., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.

T 31 S R 6 W WM
 S 1/4 S 9
 S 16
 RLS 430
 1980

from which the remains of bearing trees marked by Shaner

A fir snag, 36 ins. diam., bears S. 24° E.,
29 lks. dist., with scribe marks 1/4 S16 BT
visible on open blaze.

A madrone, 8 ins. diam., bears S. 8 1/2° W.,
33 lks. dist., with scribe marks 1/4S S16 BT
visible on open double blaze.

A fir, 42 ins. diam., bears N. 58 1/2° W.,
24 lks. dist., with scribe marks 1/4S S9 BT
visible on open double blaze.

N. 88° 25' W., beginning new measurement.

Descend 205 ft. over NW. slope.

- 1.40 Dirt road, 20 lks. wide, bears N. 40° E. and S. 40° W.
- 6.90 Creek, 10 lks. wide, course N. 55° E.; asc. 820 ft. over SE. slope.
- 37.50 Spur, slopes S. 50° E.; desc. 45 ft. over S. slope.
- 40.00 The cor. of secs. 8, 9, 16, and 17, perpetuated by Milo E. Godfrey, Deputy County Surveyor, in 1964, as described in a Douglas County Surveyor's Record, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 31 S
 S 8 | S 9
 S 17 | S 16
 R 6 W
 1964