

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **17308**
T. 31 S., R. 6 W., Willamette Meridian, Oregon

CHAINS
78.68

The cor. of secs. 4, 5, 8, and 9.

Land, mountainous.
Soil, rocky clay.
Timber, fir, cedar, ash, maple, oak, madrone, yew, hemlock, and alder; undergrowth, poison oak, arrowwood, hazel, salmonberry, blackberry, huckleberry, Oregon grape, fern, manzanita, salal, rhododendron, and young timber.

Subdivision of Section 1,
T. 31 S., R. 6 W., Willamette Meridian, Oregon

From the 1/4 sec. cor. of secs. 1 and 12, perpetuated by John M. Powell, Deputy County Surveyor, in 1966, as described in a Douglas County Surveyor's Record, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 31 S R 6 W
1/4 $\frac{S 1}{S 12}$
1966

from which the remains of the original bearing trees

A fir stump, 40 ins. diam., bears N. 20° E.,
40 lks. dist., no marks visible.

A fir snag, 10 ins. diam., bears S. 50 3/4° W.,
39 lks. dist., no marks visible. (Record,
S. 49° W., 47 lks.)

and the remains of a bearing tree by Powell

A fir snag, 25 ins. diam., bears S. 4° E.,
95 1/2 lks. dist., with healed blaze.

and new bearing trees

A fir, 6 ins. diam., bears S. 34° W., 10 lks.
dist., mkd. 1/4 S12 BT.

A fir, 6 ins. diam., bears N. 24 1/2° W., 40 lks.
dist., mkd. 1/4 S1 BT.

N. 0° 16' E., on the N. and S. center line of sec. 1.

Ascend 20 ft. over broken SW. slope, through heavy timber and dense undergrowth.

4.75 Head of ravine, drains S. 50° W.; asc. 55 ft. over SW. slope.

9.35 Ridge, bears N. 70° W. and S. 55° E.; desc. 325 ft. over broken NE. slope, also dirt road, 15 lks. wide, bears N. 70° W. and S. 55° E.

17.70 Ravine, drains N. 25° W.; desc. 280 ft. over broken NW. slope.