

County Surveyor's Record, Douglas County, Oregon

17310

Subdivision of Section 1,
T. 31 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
81.55	<p>The 1/4 sec. cor. of secs. 1 and 36 on the N. bdy. of the Tp.</p> <p>From the 1/4 sec. cor. of sec. 1 only, on the E. bdy. of the Tp., established by George W. Hyde in 1855, perpetuated by Gary Langlitz, Deputy County Surveyor, in 1979, monumented with the remains of the original corner tree, a Douglas fir snag, 11 ins. diam., with scribe marks 1/4 S visible on opened blaze on W. face, from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears S. 87° W., 8 lks. dist., with a healed blaze.</p> <p>and bearing trees and a reference monument established by Langlitz in 1979</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 36° E., 13 lks. dist., with scribe marks 1/4 S6 CS BT visible on open double blaze.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 34° E., 42 1/2 lks. dist., with scribe marks 1/4 S6 CS BT visible on open double blaze.</p> <p style="padding-left: 40px;">An iron post, 1 1/4 ins. diam., firmly set, projecting 2 ins. above ground, bears S. 2° E., 7 1/2 lks. dist., with brass cap mkd. Douglas County Surveyor T31S R5W R6W WC 1/4 S1 S6 1979.</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears S. 17 1/2° W., 66 1/2 lks. dist., with scribe marks 1/4 S1 CS BT visible on bark.</p> <p>From this point, the point established by William P. Wright in 1878, as the 1/4 sec. cor. of secs. 1 and 6, bears N. 20° 13' W., 1.14 chs. dist., determined at record bearing and dist. from the remains of the Wright bearing trees</p> <p style="padding-left: 40px;">A root hole, bears North, 19 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A fir snag, 12 ins. diam., bears S. 37 1/2° E., 18 lks. dist., with scribe marks S visible on opened blaze.</p> <p>This junior point controls the bearing of the E. and W. center line of sec. 6, T. 31 S., R. 5 W. It does not control the range line bet. secs. 1 and 6.</p> <p>No permanent monument established.</p> <p>S. 89° 58' W., on the E. and W. center line of sec. 1.</p> <p>Descend 50 ft. over NW. slope, through heavy timber and dense undergrowth.</p>
1.35	Head of ravine, drains N. 25° W.; asc. 45 ft. over NE. slope.
4.35	Spur, slopes N. 20° W.; desc. 160 ft. over NW. slope.
8.65	Ravine, drains N. 20° W.; asc. 140 ft. over NE. slope.
15.15	Top of ascent, slopes North; desc. 10 ft. over NW. slope.