

# County Surveyor's Record, Douglas County, Oregon

**17311**

Subdivision of Section 1,  
T. 31 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
16.30	Spur, slopes N. 35° W.; desc. 160 ft. over broken SW. slope.
22.70	Ravine, drains N. 45° W.; asc. 110 ft. over NE. slope.
27.60	Spur, slopes N. 25° W.; desc. 225 ft. over NW. slope.
36.05	Ravine, drains S. 40° W.; asc. 25 ft. over SE. slope.
37.75	Spur, slopes S. 35° W.; desc. 45 ft. over SW. slope.
41.04	Ravine, drains S. 30° W.; asc. 5 ft. over SE. slope.
41.04	The center 1/4 sec. cor. of sec. 1.  Ascend 20 ft. over SE. slope.
42.45	Spur, slopes S. 35° W.; desc. 205 ft. over broken SW. slope.
50.35	Shoestring Creek, 5 lks. wide, course N. 30° W.; asc. 75 ft. over NE. slope.
53.30	Spur, slopes North; desc. 40 ft. over NW. slope.
55.25	Ravine, drains N. 30° E.; asc. 170 ft. over NE. slope.
60.00	Spur, slopes N. 10° W.; desc. 5 ft. over NW. slope.
61.20	Point for the center W 1/16 sec. cor. of sec. 1.  Set an aluminum post, 28 ins. long., 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.  <div style="text-align: center;"> <math display="block">C \frac{W \frac{1}{16}}{S \ 1} C</math> <p>1981</p> </div> from which  A fir, 8 ins. diam., bears S. 68 1/2° W., 20 lks. dist., mkd. CW 1/16 S1 BT.  A fir, 10 ins. diam., bears N. 15° W., 18 lks. dist., mkd. CW 1/16 S1 BT.  Descend 80 ft. over NW. slope.
66.40	Ravine, drains N. 20° E.; asc. 45 ft. over NE. slope.
68.65	Spur, slopes N. 35° E.; desc. 20 ft. over NW. slope.
69.70	Ravine, drains N. 35° E.; asc. 220 ft. over broken NE. slope.
81.36	The 1/4 sec. cor. of secs. 1 and 2.
	From the center W 1/16 sec. cor. of sec. 1.  N. 0° 15' E., on the N. and S. center line of the NW 1/4 of sec. 1.  Descend 25 ft. along spur top, through heavy timber and dense undergrowth.
2.10	Spur, slopes N. 40° E. from S. 10° E.; desc. 260 ft. over NW. slope.