

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 1,
T. 31 S., R. 6 W., Willamette Meridian, Oregon

17312

CHAINS	
9.20	Creek, 2 lks. wide, course N. 80° E.; asc. 50 ft. over SE. slope.
11.35	Spur, slopes East; desc. 55 ft. over NE. slope.
14.30	Head of ravine, drains N. 50° E.; asc. 20 ft. over SE. slope.
20.03	Point for the NW 1/16 sec. cor. of sec. 1, at intersection with the E. and W. center line of the NW 1/4 of sec. 1. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. NW 1/16 S 1 1981 from which A fir, 15 ins. diam., bears S. 86° E., 11 1/2 lks. dist., mkd. NW 1/16 S1 BT. A fir, 15 ins. diam., bears S. 85 1/2° W., 25 1/2 lks. dist., mkd. NW 1/16 S1 BT. Ascend 5 ft. over SE. slope.
21.25	Spur, slopes N. 30° E.; desc. 60 ft. over NW. slope.
23.45	Head of ravine, drains N. 55° E.; desc. 10 ft. over NE. slope.
25.95	Spur, slopes N. 10° E.; desc. 140 ft. along NW. slope.
34.15	Head of ravine, drains N. 80° E.; desc. 80 ft. over NE. slope.
41.15	The W 1/16 sec. cor. of secs. 1 and 36 on the N. bdy. of the Tp.
	From the center N 1/16 sec. cor. of sec. 1. S. 89° 48' W., on the E. and W. center line of the NW 1/4 of sec. 1. Descend 225 ft. over SE. slope, through heavy timber and dense undergrowth.
5.90	Ravine, drains N. 45° W.; asc. 5 ft. over NE. slope.
7.50	Spur, slopes N. 35° W.; desc. 100 ft. over NW. slope.
11.10	Shoestring Creek, 5 lks. wide, course N. 25° E.; asc. 350 ft. over SE. slope.
20.14	The NW 1/16 sec. cor. of sec. 1. Ascend 40 ft. over SE. slope.
21.55	Spur, slopes N. 25° E.; desc. 60 ft. over SW. slope.
25.90	Ravine, drains N. 35° W.; asc. 40 ft. over NE. slope.
28.65	Spur, slopes N. 30° W.; desc. 240 ft. over NW. slope.
36.80	Creek, 2 lks. wide, course N. 20° E.; asc. 170 ft. over broken NE. slope.