

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **17316**
 T. 21 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

T 21 S R 5 W
 1/4
 S 32 | S 33
 1981

from which new bearing trees

A fir, 24 ins. diam., bears N. 63 1/4° E., 46 lks. dist., mkd. 1/4 S33 BT.

A fir, 24 ins. diam., bears N. 34° W., 4 lks. dist., mkd. 1/4 S32 BT.

N. 0° 14' W., bet. secs. 32 and 33, marking and blazing the true line.

Ascend 345 ft. over broken SE. slope, through heavy timber and dense undergrowth.

29.00 Ridge, bears N. 30° E. and S. 20° W.; desc. 210 ft. over NW. slope.

38.55 Creek, 1 lk. wide, course S. 75° W.; asc. 15 ft. over broken SW. slope.

40.00 Ravine, drains S. 10° W.; asc. 5 ft. over SE. slope.

40.16 The cor. of secs. 28, 29, 32, and 33, perpetuated by person(s) unknown, monumented with an iron rod, 1/2 in. diam., firmly set, projecting 6 ins. above ground, from which the remaining original bearing trees

A fir, 65 ins. diam., bears N. 63° E., 53 lks. dist., with fragmentary scribe marks visible on bark blaze.

A cedar, 34 ins. diam., bears S. 50 1/2° W., 102 lks. dist., with healed blaze. (Record, S. 55° W., 110 lks.)

A fir, 60 ins. diam., bears N. 88° W., 86 lks. dist., with scribe marks S29 T21S R5 visible on bark blaze. (Record, N. 84° W., 94 lks.)

At the corner point

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, with aluminum cap mkd.

T 21 S R 5 W
 S 29 | S 28
 S 32 | S 33
 1981

*FD OK 2-1994
 H. Christenson
 M118-63*

from which a new bearing tree

A grand fir, 16 ins. diam., bears S. 6 1/4° E., 55 lks. dist., mkd. T21S R5W S33 BT.

From this point, a witness corner established by Milo E. Godfrey, Deputy County Surveyor, in 1962, bears North, 0.303 chs. dist., monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with