

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **17318**  
T. 21 S., R. 5 W., Willamette Meridian, Oregon

**CHAINS**

Ascend 540 ft. over broken SE. slope, through heavy timber and dense undergrowth.

39.92

Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 21 S    R 5 W  
1/4  $\frac{S 28}{S 33}$

1981

from which

A fir, 8 ins. diam., bears N. 47 1/2° E., 33 lks. dist., mkd. 1/4 S28 BT.

A fir, 6 ins. diam., bears S. 25 1/4° W., 60 lks. dist., mkd. 1/4 S33 BT.

From this point, a corner established by Malcolm N. Clark, Registered Land Surveyor, No. 601, in 1972, bears S. 75° 38' E., 0.165 chs. dist., monumented with an aluminum post, 2 ins. diam., firmly set, projecting 2 ins. above ground, with aluminum cap mkd. Green Empire Inc T21S R5W S 1/4 S28 S33 1972, from which bearing trees mkd. by Clark

A fir, 10 ins. diam., bears N. 57 3/4° E., 68 lks. dist., with healed double blaze.

A fir, 10 ins. diam., bears S. 1° E., 62 lks. dist., with healed double blaze.

Ascend 135 ft. over broken SE. slope.

53.20

Ridge, bears N. 75° W. and S. 75° E.; desc. 130 ft. over broken SW. slope.

59.88

Point for the W 1/16 sec. cor. of secs. 28 and 33.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

W 1/16  $\frac{S 28}{S 33}$

1981

from which

A fir, 48 ins. diam., bears N. 15° E., 8 lks. dist., mkd. W 1/16 S28 BT.

A fir, 8 ins. diam., bears S. 57° E., 37 lks. dist., mkd. W 1/16 S33 BT.

Descend 70 ft. over SW. slope.

61.65

Ravine, drains SW.; asc. 40 ft. over SE. slope.

69.90

Ridge, bears N. 55° E. and S. 55° W.; desc. 230 ft. over NW. slope.

76.90

Ravine, drains S. 60° W.; asc. 10 ft. over SE. slope.