

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **17320**
T. 21 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 $\frac{S\ 29}{S\ 32}$

1981

from which

A cedar, 18 ins. diam., bears N. 45° W., 18 1/2 lks. dist., mkd. W 1/16 S29 BT.

A fir, 8 ins. diam., bears S. 46 1/2° W., 43 lks. dist., mkd. W 1/16 S32 BT.

Ascend 175 ft. over NE. slope.

63.75 Gravelled driveway, 15 lks. wide, bears N. 30° E. and S. 30° W.

64.10 Gravelled driveway, 15 lks. wide, bears N. 20° E. and S. 20° W.

65.15 Power line, bears N. and S.

67.50 Smith River Road, asphalt surfaced, 40 lks. wide, bears N. 70° W. and S. 50° E.

73.25 Gravelled driveway, 20 lks. wide, bears N. 35° E. and S. 40° W.

77.25 Gravelled driveway, 20 lks. wide, bears N. 50° W. and S. 70° E.

79.24 The cor. of secs. 29, 30, 31, and 32, perpetuated and recorded by Floyd C. Frear, Deputy County Surveyor, in 1924, further perpetuated and recorded by Ronald W. VanDomelen, Registered Land Surveyor, No. 761, in 1969, and still further perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1970, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 21 S R 5 W

S 30 | S 29
S 31 | S 32

1970

from which the remains of the original bearing trees

A root hole, bears N. 58° E., 57 lks. dist.

A decayed fir stump, size indeterminate, bears S. 77° E., 40 lks. dist., no marks visible.

and bearing trees mkd. by VanDomelen

A fir, 12 ins. diam., bears N. 29° E., 35 lks. dist., with healed blaze.

A fir, 15 ins. diam., bears N. 77 3/4° E., 14 lks. dist., with healed blaze.

and bearing trees mkd. by Tracy

A grand fir, 20 ins. diam., bears S. 4° E., 79 lks. dist., with healed blaze.

*Cor. Fd. OK
DCSO - 11/20/71
C.S. 6/1/21*