

County Surveyor's Record, Douglas County, Oregon

17323

Subdivision of Section 29
T. 21 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

N. 0° 33' W., on the N. and S. center line of sec. 29.
Ascend 75 ft. over broken SE. slope, through heavy timber and dense undergrowth.


10.00 Ridge, bears N. and S. 10° W.; asc. 25 ft. along ridge top.

16.25 Leave ridge, bears N. 15° W. and S.; asc. 15 ft. over SE. slope.

19.60 Woven wire fence, extends E. and W.

19.87 Point for the center S 1/16 sec. cor. of sec. 29.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.



from which

A fir, 14 ins. diam., bears N. 56 1/2° E., 53 lks. dist., mkd. CS 1/16 S29 BT.

A fir, 16 ins. diam., bears S. 12 3/4° W., 45 1/2 lks. dist., mkd. CS 1/16 S29 BT.

Ascend 70 ft. over SE. slope.

24.70 Ridge, bears E. and W.; desc. 180 ft. over NE. slope, also dirt road, 20 lks. wide, bears E. and W.

35.50 Spur, slopes N. 35° E.; desc. 140 ft. over NW. slope.

39.20 Ravine, drains N. 10° E.; desc. 5 ft. over NE. slope.

39.74 Point for the center 1/4 sec. cor. of sec. 29, at intersection with the E. and W. center line.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

BK
 2-94 4112-63

T 21 S R 5 W

C 1/4 S 29

1981

from which

A fir, 6 ins. diam., bears N. 44° E., 33 lks. dist., mkd. C 1/4 S29 BT.

A fir, 11 ins. diam., bears S. 16° W., 57 lks. dist., mkd. C 1/4 S29 BT.

Descend 10 ft. over NE. slope.

46.85 Spur, slopes N. 30° E.; desc. 370 ft. over NW. slope.

73.30 Ellenburg Creek, 15 lks. wide, course S. 40° E.; asc. 80 ft. over SW. slope.