

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 29,
T. 21 S., R. 5 W., Willamette Meridian, Oregon

17324

CHAINS

74.60

Dirt road, 20 lks. wide, bears N. 55° W. and S. 80° E.

75.24

Power line, bears N. 40° W. and S. 40° E.

80.37

The 1/4 sec. cor. of secs. 20 and 29, perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor, No. 239, in 1962, monumented with a wood post, 3 ins. square, firmly set, projecting 12 ins. above ground, with scribe marks 1/4 S visible on N. face, from which the remains of an original bearing tree

A sawed fir stump, 48 ins. diam., bears N. 51° W.,
69 lks. dist., with axe marks visible on bark.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 21 S R 5 W
1/4 S 20
 S 29
1981

from which new bearing trees

A fir, 11 ins. diam., bears N. 6 1/2° E., 36 lks. dist., mkd. 1/4 S20 BT.

A fir, 6 ins. diam., bears S. 41° W., 22 1/2 lks. dist., mkd. 1/4 S29 BT.

Reset the wood post alongside the iron post.

The corner is located at intersection of wire fences extending generally S., E., W.

From the 1/4 sec. cor. of secs. 28 and 29, perpetuated and recorded by Oscar F. Thiel, Deputy County Surveyor, in 1940, from original evidence no longer in existence, and further perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1962, monumented with an iron pipe, 1/2 in. diam., firmly set, projecting 18 ins. above ground, from which the remains of bearing trees mkd. by Thiel

A fir, 40 ins. diam., bears N. 18 1/2° E.,
32 1/2 lks. dist., with healed double blaze.

A cedar stump, 16 ins. diam., bears N. 73° W.,
61 lks. dist., no marks visible.

and the remains of a bearing tree mkd. by Godfrey

A sawed cedar stump, 36 ins. diam., bears N. 86° W.,
58 lks. dist., no marks visible.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 21 S R 5 W
 1/4
S 29 | S 28
 1981

*OK 2-94
MIB-
H. Christensen*