

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 29,
T. 21 S., R. 5 W., Willamette Meridian, Oregon

17326

| CHAINS | |
|--------|--|
| | <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">SW 1/16</p> <p style="text-align: center;">S 29</p> <p style="text-align: center;">1981</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 11 1/2° E., 11 1/2 lks. dist., mkd. SW 1/16 S29 BT.</p> <p style="padding-left: 40px;">A cedar, 16 ins. diam., bears N. 36 1/2° W., 25 lks. dist., mkd. SW 1/16 S29 BT.</p> <p>Ascend 200 ft. over SW. slope.</p> |
| 39.64 | The center W 1/16 sec. cor. of sec. 29. |
| | <p>From the center S 1/16 sec. cor. of sec. 29.</p> <p>N. 89° 31' W., on the E. and W. center line of the SW 1/4 of sec. 29.</p> <p>Ascend 25 ft. over SE. slope, through heavy timber and dense undergrowth.</p> |
| 1.30 | Ridge, bears N. 25° W. and S. 25° E.; desc. 330 ft. over broken SW. slope. |
| 2.55 | Woven wire fence, extends N. and S. |
| 19.78 | The SW 1/16 sec. cor. of sec. 29. |
| | Descend 80 ft. over SW. slope. |
| 21.35 | Creek, 1 lk. wide, course S. 35° W.; asc. 20 ft. over SE. slope. |
| 22.50 | Spur, slopes S. 30° W.; desc. 170 ft. over SW. slope. |
| 34.50 | Fitch Creek, 10 lks. wide, course S. 25° E.; asc. 40 ft. over NE. slope. |
| 37.90 | Spur, slopes NW.; desc. 35 ft. over NW. slope. |
| 38.10 | Power line, bears N. and S. |
| 39.15 | Creek, 5 lks. wide, course N. 55° E.; asc. 15 ft. over SE. slope. |
| 39.56 | The S 1/16 sec. cor. of secs. 29 and 30. |
| | <p>Subdivision of Section 29³³, T. 21 S., R. 5 W., Willamette Meridian, Oregon</p> |
| | <p>From the 1/4 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp., perpetuated and recorded by J. W. Cole, Deputy County Surveyor, in 1924, from original evidence no longer in existence, and further perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1964, monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 2 ins. above ground, from which the remains of bearing trees mkd, by Cole.</p> |