

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 33,
T. 21 S., R. 5 W., Willamette Meridian, Oregon

17328

CHAINS	
	Ascend 165 ft. over broken SE. slope.
64.60	Spur, slopes S. 80° E.; desc. 50 ft. over NE. slope.
70.05	Bottom of descent, slopes E.; asc. 25 ft. over broken SE. slope.
80.05	The 1/4 sec. cor. of secs. 28 and 33.
<p>From the 1/4 sec. cor. of secs. 33 and 34, perpetuated and recorded by Ben B. Irving, Deputy County Surveyor, in 1938, determined at record bearing and distance from the remains of an original bearing tree</p> <p style="margin-left: 40px;">A decayed fir stump, size indeterminate, bears S. 37° E., 162 lks. dist., no marks visible.</p> <p>and the remains of a bearing tree mkd. by Irving</p> <p style="margin-left: 40px;">A fir stump, 24 ins. diam., bears N. 62° W.; 75 lks. dist., with scribe marks BT visible on opened blaze.</p> <p>At the corner point</p> <p style="margin-left: 40px;">Seat a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in drill hole, in exposed bedrock, with top mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 21 S R 5 W</p> <p style="margin-left: 100px;">1/4</p> <p style="margin-left: 80px;">S 33 S 34</p> <p style="margin-left: 100px;">1981</p> </div> <p>from which new bearing trees</p> <p style="margin-left: 40px;">An oak, 22 ins. diam., bears S. 60° E., 97 lks. dist., mkd. 1/4 S34 BT.</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears N. 25 1/2° W., 60 lks. dist., mkd. 1/4 S33 BT.</p> <p>From this point, a corner established and recorded by Wilford N. Haines, Registered Land Surveyor, No. 239, in 1959, bears N. 58° W., 0.15 chs. dist., monumented with a "T" shaped iron rod, 1 in. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. Wilford N. Haines 239 Survey Point Drain Ore., from which the remains of bearing trees mkd. by Milo E. Godfrey, Deputy County Surveyor, in 1964</p> <p style="margin-left: 40px;">A fir snag, 24 ins. diam., bears N. 12° E., 62 lks. dist., with scribe marks 1/4 S34 CS BT visible on open blaze.</p> <p style="margin-left: 40px;">An oak, 14 ins. diam., bears N. 28 1/2° W., 17 lks. dist., with healed double blaze.</p> <p>N. 89° 46' W., on the E. and W. center line of sec. 33.</p> <p>Descend 10 ft. over broken SW. slope, through heavy timber and dense undergrowth.</p>	
1.20	Creek, 3 lks. wide, course S. 60° E.; asc. 115 ft. over NE. slope.