

County Surveyor's Record, Douglas County, Oregon

17333

Dependent Resurvey, Portion of E. Bdy.,
T. 24 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

T 24 S |
1/4 S 25 |
R 2 W |
1967

from which bearing trees mkd. by Roseberry

A fir, 36 ins. diam., bears S. 66 1/2° W., 71 1/2 lks. dist., with healed blaze.

A fir, 33 ins. diam., bears N. 45° W., 66 1/2 lks. dist., with healed blaze.

N. 6° 53' E., on the E. bdy. of sec. 25, marking and blazing the true line.

Ascend 10 ft. over SW. slope, through scattering timber and dense undergrowth.

0.80 Rocky spur, slopes N. 15° W.; desc. 130 ft. over NW. slope.

4.95 Creek, 12 lks. wide, course S. 80° W.; asc. 55 ft. over SW. slope.

9.60 Spur, slopes S. 70° W.; desc. 250 ft. over broken NW. slope.

21.50 Gravelled road, 30 lks. wide, bears N. 85° E. and N. 85° W.

24.00 Northeast Fork of Rock Creek, 30 lks. wide, course W.; asc. 155 ft. over SE. slope.

29.92 True point for the closing cor. of secs. 19 and 30, T. 24 S., R. 1 W., hereinafter described.

38.90 The cor. of secs. 24 and 25 only, T. 24 S., R. 2 W., monumented with an iron post, 1 in. diam., firmly set, projecting 1 in. above rock outcrop, with brass cap mkd.

T 24 S | T 24 S
S 24 | R 1 W

S 25 | S 19
R 2 W

1967

from which a bearing object and the remains of a bearing tree mkd. by Roseberry

A rock outcrop, bears S. 60° W., 10 lks. dist., with fragmentary chisel marks visible on E. face.

A root hole, bears N. 51° W., 97 lks. dist., with down fir alongside, 38 ins. diam., with fragmentary scribe marks visible on decayed blaze.

and a new bearing object

A rock outcrop, bears N. 25° W., 19 lks. dist., mkd. X B0.