

County Surveyor's Record, Douglas County, Oregon

17335

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 1 W., Willamette Meridian, Oregon

CHAINS

7.00

Gravelled road, 20 lks. wide, bears N. 55° W. and S. 55° E.


19.10

Spur, slopes N. 75° E.; desc. 10 ft. over broken NE. slope.

19.87

Point for the S 1/16 sec. cor. of secs. 20 and 21.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.



from which

A fir, 10 ins. diam., bears S. 83° E., 17 1/2 lks. dist., mkd. S 1/16 S21 BT.


A fir, 8 ins. diam., bears N. 32° W., 32 1/2 lks. dist., mkd. S 1/16 S20 BT.

Descend 205 ft. over broken NE. slope.

39.74

The 1/4 sec. cor. of secs. 20 and 21, perpetuated and recorded by Milo E. Godfrey, Deputy Douglas County Surveyor, in 1961, further perpetuated and recorded by Vernon R. Tracy, Deputy Douglas County Surveyor, in 1970, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE



from which the remains of an original bearing tree

A sawed fir stump, 36 ins. diam., bears N. 14 1/2° W., 35 lks. dist., with healed blaze.

and remains of the bearing trees mkd. by Godfrey

A hemlock, 15 ins. diam., bears N. 8° E., 22 lks. dist., with healed blaze.

A yew snag, 8 ins. diam., bears N. 82° W., 5 1/2 lks. dist., with scribe marks BT visible on open blaze.

and a bearing tree mkd. by Tracy

A hemlock, 20 ins. diam., bears S. 82° W., 66 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.

Land, mountainous.
Soil, rocky clay.
Timber, fir, hemlock, yew, maple, oak, madrone, cedar, alder, chinquapin, and pine; undergrowth, hazel, arrow-wood, rhododendron, manzanita, huckleberry, blackberry, salal, Oregon grape, ferns, and young timber.