

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 1 W., Willamette Meridian, Oregon

17336

CHAINS	
	From the cor. of secs. 20, 21, 28, and 29.
	S. 89° 05' W., bet. secs. 20 and 29.
	Ascend 15 ft. over SE. slope, through heavy timber and dense undergrowth.
0.95	Ridge, bears N. 20° E. and S. 15° W.; desc. 615 ft. over NW. slope.
2.40	Gravelled road, 25 lks. wide, bears N. and S. 20° W.
17.60	Ravine, drains S. 40° E.; asc. 10 ft. over SE. slope.
19.67	Point for the E 1/16 sec. cor. of secs. 20 and 29.
	Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	$E \frac{1}{16} \frac{S \ 20}{S \ 29}$
	1982
	from which
	A fir, 8 ins. diam., bears N. 29 1/2° E., 65 lks. dist., mkd. E 1/16 S20 BT.
	A cedar, 8 ins. diam., bears S. 12 1/2° E., 28 1/2 lks. dist., mkd. E 1/16 S29 BT.
	Ascend 105 ft. over SE. slope.
25.10	Spur, slopes S. 35° W.; desc. 325 ft. over SW. slope.
39.34	The 1/4 sec. cor. of secs. 20 and 29, perpetuated and recorded by Howard W. Johnstone, Registered Land Surveyor, No. 498, in 1977, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground, with an aluminum cap mkd.
	$\frac{1}{4} \frac{20}{29}$
	from which the original bearing trees
	A fir, 24 ins. diam., bears S. 65° E., 15 lks. dist., with healed double blaze.
	A cedar, 17 ins. diam., bears N. 3° W., 29 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.
	—————
	S. 89° 43' W., beginning a new measurement.
	Descend 180 ft. over SW. slope.
6.25	Creek, 10 lks. wide, course N. 40° W.; asc. 10 ft. over NE. slope.
13.40	Spur, slopes N. 10° W.; desc. 45 ft. over NW. slope.
15.25	Ravine, drains N. 5° W.; asc. 165 ft. over broken NE. slope.