

County Surveyor's Record, Douglas County, Oregon

17337

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 1 W., Willamette Meridian, Oregon

CHAINS

19.65

The W 1/16 sec. cor. of secs. 20 and 29, established by Howard W. Johnstone, Registered Land Surveyor, No. 498, in 1977, and accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 9 ins. above the ground, with aluminum cap mkd.

W 1/16 $\frac{S\ 20}{S\ 29}$

from which bearing trees mkd. by Johnstone

A fir, 19 ins. diam., bears N. 32° E., 13 lks. dist., with healed blaze.

A hemlock, 9 ins. diam., bears S. 77° E., 12 1/2 lks. dist., with scribe marks 1/16 BT visible on partially healed blaze.

S. 89° 51' W., beginning a new measurement.

Descend 130 ft. over NW. slope.

12.00

Creek, 8 lks. wide, course N. 10° W.; asc. 295 ft. over NE. slope.

19.65

The cor. of secs. 19, 20, 29, and 30, perpetuated and recorded by Vernon R. Tracy, Deputy Douglas County Surveyor, in 1966, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 24 S

S 19	S 20
S 30	S 29

R 1 W

1966

from which the remains of the original bearing trees

A sawed fir stump, 30 ins. diam., bears N. 73° E., 39 lks. dist., with healed blaze.

A sawed fir stump, 20 ins. diam., bears S. 42° E., 39 lks. dist., with healed blaze.
(Record, S. 45° E.)

A root hole, bears S. 27° W., 22 lks. dist., with down sawed fir stump alongside, 12 ins. diam., no marks visible.

A root hole, bears N. 33° W., 10 lks. dist., with down cedar alongside, 22 ins. diam., no marks visible.

and the remains of a bearing tree mkd. by Tracy

A sawed hemlock stump, 12 ins. diam., bears N. 9° W., 35 lks. dist., with healed blaze.

and new bearing trees

A sawed fir stump, 40 ins. diam., bears S. 72 1/2° W., 51 1/2 lks. dist., mkd. T24S R1W S30 BT.