

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 1 W., Willamette Meridian, Oregon

17338

CHAINS	
	<p style="text-align: center;">A sawed fir stump, 42 ins. diam., bears N. 34 1/4° W., 81 1/2 lks. dist., mkd. T24S RIW S19 BT.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, cedar, hemlock, maple, oak, madrone, alder, pine, yew, and chinquapin; undergrowth, salal, arrowwood, Oregon grape, rhododendron, huckleberry, salmonberry, ferns, blackberry, hazel, and young timber.</p>
	<p style="text-align: center;">N. 89° 18' W., bet. secs. 19 and 30.</p> <p>Ascend 10 ft. over NE. slope, through scattering timber and dense undergrowth.</p>
0.80	<p>Spur, slopes N. 75° W.; desc. 615 ft. over broken NW. slope.</p>
23.60	<p>Creek, 6 lks. wide, course S. 70° W.; asc. 95 ft. over SW. slope.</p>
33.55	<p>Gravelled road, 20 lks. wide, bears N. 40° E. and S. 40° W.</p>
37.65	<p>Spur, slopes S. 10° E.; desc. 30 ft. over SW. slope.</p>
40.16	<p>The 1/4 sec. cor. of secs. 19 and 30, perpetuated and recorded by Larry E. Monrean, Deputy Douglas County Surveyor, in 1977, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p>
<p>COUNTY SURVEYORS OFFICE</p> <p style="margin-left: 100px;">T 24 S R 1 W</p> <p style="margin-left: 100px;">1/4 $\frac{S 19}{S 30}$</p> <p style="margin-left: 100px;">1977</p>	
<p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A root hole, bears S. 52° E., 5 lks. dist., with down fir alongside, 12 ins. diam., with scribe marks BT visible on opened blaze.</p> <p style="margin-left: 40px;">A root hole, bears N. 19° W., 40 lks. dist., with down fir alongside, 12 ins. diam.; no marks visible.</p> <p>and bearing trees mkd. by Monrean</p> <p style="margin-left: 40px;">A fir, 32 ins. diam., bears N. 85° E., 23 lks. dist., with scribe marks 1/4 S19 CS BT visible on open blaze.</p> <p style="margin-left: 40px;">A sawed fir stump, 60 ins. diam., bears S. 65 1/4° W., 109 lks. dist., with railroad spike driven in top, mkd. BO on head.</p> <p style="margin-left: 40px;">A hemlock, 13 ins. diam., bears N. 7° W., 65 lks. dist., with scribe marks 1/4 S19 CS BT visible on open blaze.</p>	
<p style="text-align: center;">N. 89° 24' W., beginning a new measurement.</p>	