

County Surveyor's Record, Douglas County, Oregon

17339

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 1 W., Willamette Meridian, Oregon

CHAINS

Descend 35 ft. over SW. slope.

0.55 Creek, 2 lks. wide, course S. 40° E.; asc. 110 ft. over SE. slope.

3.90 Spur, slopes S. 5° E.; desc. 60 ft. over SW. slope.

8.30 Ravine, drains S. 35° E.; asc. 480 ft. over SE. slope.

18.90 Spur, slopes S. 40° E.; desc. 985 ft. over SW. slope.

49.40 Creek, 12 lks. wide, course N. 60° W.; desc. 80 ft. over broken SW. slope.

70.05 Creek, 20 lks. wide, course S. 75° W.; asc. 315 ft. over SE. slope.

91.20 Spur, slopes S. 30° W.; desc. 400 ft. over SW. slope.

99.60 Northeast Fork of Rock Creek, 30 lks. wide, course S. 15° W.; asc. 135 ft. over SE. slope.

102.26 The original closing cor. of secs. 19 and 30, perpetuated and recorded by Bruce A. Shaner, Registered Land Surveyor, No. 430, in 1965, further perpetuated and recorded by Vernon R. Tracy, Deputy Douglas County Surveyor, in 1966, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 24 S R 1 W

S 19	R
S 30	W

CC
1966

from which the remaining original bearing tree

A fir, 33 ins. diam., bears N. 19° E., 12 lks. dist., with fragmentary scribe marks visible on opened blaze. (Record, N. 29° E.)

and a bearing tree mkd. by Shaner

A fir, 55 ins. diam., bears S. 13 3/4° E., 108 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

This is now an amended cor. Add the marks AM to the brass cap.

102.35 Intersect the E. bdy. of sec. 25, T. 24 S., R. 2 W.

True point for the closing cor. of secs. 19 and 30.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 S T 24 S

R 2 W	S 19	CC
S 25	S 30	
	R 1 W	

1981