

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **17340**
T. 24 S., R. 1 W., Willamette Meridian, Oregon

CHAINS			
	<p>from which</p> <p style="margin-left: 40px;">A fir, 38 ins. diam., bears N. 16° E., 111 lks. dist., mkd. T24S R1W S19 CC BT.</p> <p style="margin-left: 40px;">A fir, 4 ins. diam., bears S. 36° E., 75 lks. dist., mkd. X BT.</p> <p>From this point, the cor. of secs. 24 and 25 only, T. 24 S., R. 2 W., hereinbefore described, bears N. 6° 53' E., 8.98 chs. dist.</p> <p>Land mountainous. Soil, rocky clay. Timber, cedar, fir, hemlock, yew, pine, oak, alder, madrone, maple, and chinquapin; undergrowth, salal, rhododendron, Oregon grape, vine maple, fern, arrowwood, huckleberry, blackberry, and young timber.</p>		
	<p>From the cor. of secs. 19, 20, 29, and 30.</p> <p>N. 0° 15' E., bet. secs. 19 and 20.</p> <p>Descend 445 ft. over NE. slope, through scattering timber and dense undergrowth.</p>		
2.40	Dirt road, 20 lks. wide, bears N. 80° W. and S. 60° E.		
10.95	Creek, 15 lks. wide, course N. 60° W.; asc. 95 ft. over SW. slope.		
18.80	Base of rock bluff, bears NW. and SE.; asc. 80 ft.		
19.705	<p>Point for the S 1/16 sec. cor. of secs. 19 and 20.</p> <p>Set a brass tablet, 3 1/2 ins. diam., 3 1/4 in. stem, in face of rock bluff, mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>S 1/16</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 19</td> <td style="padding: 0 5px;">S 20</td> </tr> </table> <p>1982</p> </div>	S 19	S 20
S 19	S 20		
	<p>from which</p> <p style="margin-left: 40px;">A hemlock, 19 ins. diam., bears N. 2 3/4° E., 213 lks. dist., mkd. S 1/16 S20 BT.</p> <p style="margin-left: 40px;">A hemlock, 15 ins. diam., bears N. 40 1/2° W., 141 lks. dist., mkd. S 1/16 S19 BT.</p> <p>Ascend 10 ft. over SW face of waterfall.</p>		
19.95	Top of waterfall, edge of bluff bears NW. and SE., creek, 5 lks. wide, course S. 10° W.; asc. 5 ft. over broken SW. slope.		
20.76	A witness cor. to the S 1/16 sec. cor. of secs. 19 and 20, established by Howard W. Johnstone, Registered Land Surveyor, No. 498, in 1977, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground, with aluminum cap mkd.		