


# County Surveyor's Record, Douglas County, Oregon

17341

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 24 S., R. 1 W., Willamette Meridian, Oregon

CHAINS



from which the remains of the bearing trees mkd. by Johnstone


A sawed fir stump, 18 ins. diam., bears S.  $83 \frac{1}{2}^\circ$  E., 83 lks. dist., with scribe marks 1/16 WC RP visible on open blaze.

A root hole, bears N.  $28 \frac{1}{4}^\circ$  W., 44 lks. dist., with down maple alongside, 10 ins. diam., with healed blaze.

Ascend 85 ft. over broken SW. slope.

27.30 Creek, 8 lks. wide, course S.  $10^\circ$  W.; asc. 225 ft. over SW. slope.

39.41 The  $\frac{1}{4}$  sec. cor. of secs. 19 and 20, perpetuated and recorded by Howard Johnstone, Registered Land Surveyor, No. 498, in 1977, monumented with an iron rod,  $\frac{5}{8}$  in. diam., firmly set, projecting 6 ins. above ground, with aluminum cap mkd.



from which the remains of the original bearing trees

A sawed fir stump, 37 ins. diam., bears N.  $28 \frac{1}{2}^\circ$  E., 30 lks. dist., with a healed blaze.

A fir, 46 ins. diam., bears S.  $56^\circ$  W., 55 lks. dist., with a healed blaze.

No other suitable tree available.


N.  $0^\circ 11'$  W., beginning new measurement.

Ascend 755 ft. over SW. slope.

31.40 Ridge, bears E. and W.; desc. 95 ft. over NE. slope.

39.17 The cor. of secs. 17, 18, 19, and 20, perpetuated and recorded by Milo E. Godfrey, Deputy Douglas County Surveyor, in 1961, monumented with an iron post,  $1 \frac{1}{4}$  ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE



1961

from which the remains of the original bearing trees

A fir, 22 ins. diam., bears N.  $70^\circ$  E., 44 lks. dist., with a healed blaze.