

County Surveyor's Record, Douglas County, Oregon

Subdivision of Sec. 20,
T. 24 S., R. 1 W., Willamette Meridian, Oregon

17344

CHAINS

COUNTY SURVEYORS OFFICE

T 24 S

1/4 $\frac{S\ 17}{S\ 20}$

R 1 W
1962

from which the original bearing trees

A madrone, 12 ins. diam., bears N. 50° E., 16 lks. dist., with a healed blaze.

A fir, 24 ins. diam., bears S. 22° W., 41 lks. dist., with a healed blaze. (Record, madrone)

and a bearing tree mkd. by Godfrey

A fir, 11 ins. diam., bears N. 8 1/2° E., 23 1/2 lks. dist., with a healed double blaze.

From the 1/4 sec. cor. of secs. 20 and 21.

S. 89° 10' W., on the E. and W. center line of sec. 20.

Ascend 45 ft. over broken NE. slope, through heavy timber and dense undergrowth.

6.00 Ridge, bears N. 15° E. and S.; desc. 410 ft. over NW. slope.

7.55 Gravelled road, 30 lks. wide, bears N. 30° E. and S. 5° W.

19.57 The center E 1/16 sec. cor. of sec. 20, established by Howard W. Johnstone, Registered Land Surveyor, No. 498, in 1977, and accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground, with aluminum cap mkd.

C $\frac{E\ 1/16}{S\ 20}$ C

from which the remains of the bearing trees mkd. by Johnstone

A cedar snag, 8 ins. diam., bears N. 16° E., 22 lks. dist., with scribe marks CE 1/16 BT visible on open blaze.

A cedar, 15 ins. diam., bears S. 53° W., 43 lks. dist., with scribe marks CE 1/16 BT visible on open blaze.

No bearing tree available to North.

S. 89° 13' W., beginning new measurement.

Descend 20 ft. over NW. slope.

1.25 Creek, 1 lk. wide, course S. 10° W.; asc. 255 ft. over SE. slope.

14.50 Gravelled road, 25 lks. wide, bears N. 30° E. and S. 70° W.