

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Sec. 20,  
T. 24 S., R. 1 W., Willamette Meridian, Oregon

17346

CHAINS	
	<p style="text-align: center;">A fir, 42 ins. diam., bears S. 16 1/2° E., 8 1/2 lks. dist., with scribe marks SE 1/16 S20 BT visible on open blaze.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">SE 1/16</p> <p style="text-align: center;">S 20</p> <p style="text-align: center;">1982</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 17' W., beginning new measurement.</p> <p>Descend 5 ft. over NW. slope.</p>
0.20	Ravine, drains S. 45° W.; asc. 55 ft. over SW. slope.
4.30	Spur, slopes W.; desc. 115 ft. over NW. slope.
7.30	Ravine, drains W.; asc. 145 ft. over SW. slope.
13.10	Spur, slopes W.; desc. 70 ft. over NW. slope.
19.88	The center E 1/16 sec. cor. of sec. 20.
	<p>From the S 1/16 sec. cor. of secs. 20 and 21.</p> <p>S. 89° 08' W., on the E. and W. center line of the SE 1/4 of sec. 20.</p> <p>Ascend 20 ft. over SE. slope, through heavy timber and dense undergrowth.</p>
0.90	Ridge, bears N. and S. 30° W.; desc. 605 ft. over W. slope, changing to broken NW. slope.
5.50	Gravelled road, 25 lks. wide, bears N. 10° E. and S. 35° W.
19.62	The SE 1/16 sec. cor. of sec. 20.
	<p style="text-align: center;">S. 89° 07' W., beginning new measurement.</p> <p>Descend 335 ft. over broken SW. slope.</p>
12.65	Creek, 10 lks. wide, course S. 10° W.; asc. 185 ft. over SE. slope.
19.60	The center S 1/16 sec. cor. of sec. 20.
	<p>From the W 1/16 sec. cor. of secs. 20 and 29,</p> <p>N. 0° 05' E., on the N. and S. center line of the SW 1/4 of sec. 20.</p> <p>Descend 225 ft. over NW. slope, through heavy timber and dense undergrowth.</p>
12.90	Creek, 8 lks. wide, course S. 70° W.; asc. 125 ft. over SW. slope.