

County Surveyor's Record, Douglas County, Oregon

17251 Dependent Resurvey of a Portion of the East Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

(Restoring the survey by Hezekiah H. Johnson in 1900 and resurvey by C. Albert White and Levi E. Tallett in 1951-63)

Beginning at the cor. of secs. 1 and 12 only, T. 25 S., R. 2 W., on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T 25 S	T 25 S
S 1	R 1 W
S 12	S 7
R 2 W	
1951	

from which bearing trees mkd. by White and Tallett

A sugar pine, 25 ins. diam., bears S. 38° W., 50 lks. dist., with scribe marks T25S R2W S12 BT visible on open blaze.

A fir, 48 ins. diam., bears N. 25° W., 112 lks. dist., with healed blaze. (Record, N. 20° W.)

From this point, a monument established by V. W. Hosford, Registered Land Surveyor, No. 253, in 1950, as described in a Douglas County Surveyor's Record, bears S. 29° E., 0.07 chs. dist., monumented with an iron pipe, 2 ins. diam., firmly set, projecting 10 ins. above ground, with unmarked steel cap, from which bearing trees mkd. by Hosford

A sugar pine, 23 ins. diam., bears S. 6° W., 32 1/2 lks. dist., with healed double blaze.

A fir, 50 ins. diam., bears N. 58° W., 62 lks. dist., with healed double blaze.

From this same point, United States Coast and Geodetic Survey triangulation station "MACE MOUNTAIN 1953", bears S. 13° 51' E., 301.07 chs. dist., determined at record bearing and dist. from the drill hole for the NW. reference monument. All monuments are gone.

N. 0° 11' W., on the E. bdy. of sec. 1, marking and blazing the true line.

Ascend 315 ft. over SE. slope, through heavy timber and dense undergrowth.

1.80 Gravelled road, 25 lks. wide, bears NW. and S. 80° E.

21.00 Spur, slopes E.; desc. 80 ft. over NE. slope.

33.42 The closing cor. of secs. 6 and 7, T. 25 S., R. 1 W., hereinafter described.

Descend 150 ft. over NE. slope.

38.60 Gravelled road, 30 lks. wide, bears N. 45° W. and S. 40° E.

40.10 Ravine, drains E.; asc. 5 ft. over SE. slope.

40.63 The 1/4 sec. cor. of sec. 1 only, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.