

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy.,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

17252

CHAINS

1/4 S 1 |
1951

from which bearing trees mkd. by White and Tallett

A hemlock, 19 ins. diam., bears S. 29° W.,
64 1/2 lks. dist., with healed blaze.
(Record, S. 28° W., 66 lks.)

A hemlock, 28 ins. diam., bears N. 12 3/4° W.,
49 lks. dist., with healed blaze.

From this point, a monument established by V. W. Hosford, Registered Land Surveyor, No. 253, in 1950, as described in a Douglas County Surveyor's Record, bears S. 25 1/2° E., 0.02 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 10 ins. above ground, from which bearing trees mkd. by Hosford

A hemlock, 23 ins. diam., bears S. 84° W.,
21 1/2 lks. dist., with healed blaze.

A hemlock, 27 ins. diam., bears N. 28 1/2° W.,
55 lks. dist., with healed blaze.

N. 0° 16' W., beginning new measurement.

Ascend 185 ft. over SE. slope.

1.50 Gravelled road, 30 lks. wide, bears N. 10° W. and
S. 30° W.

8.85 Gravelled road, 30 lks. wide, bears N. 35° E. and
S. 55° W.

26.15 Spur, slopes E.; desc. 60 ft. over broken NE. slope.

33.43 The 1/4 sec. cor. of sec. 6 only, T. 25 S., R. 1 W., established at proportionate dist. and recorded by V. W. Hosford, Registered Land Surveyor, No. 253, in 1950, is accepted as the cor. and is monumented with an iron pipe, 1 1/4 ins. diam., firmly set, projecting 4 ins. above ground, from which the remains of bearing trees mkd. by Hosford

A sawed fir stump, 32 ins. diam., bears N. 81° E.,
46 lks. dist., with scribe marks T25S R1W 1/4 S6
RS 253 BT visible on opened blaze.

A sawed sugar pine stump, 30 ins. diam., bears
S. 16° E., 76 1/2 lks. dist., with scribe marks
T25S R1W 1/4 S6 RS 253 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

| T 25 S
| 1/4 S 6
| R 1 W

1981

from which a new bearing tree