

County Surveyor's Record, Douglas County, Oregon

17353

Dependent Resurvey, Portion of E. Bdy.,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

A fir, 3 ins. diam., bears S. 41 3/4° E., 30 1/2 lks. dist., mkd. X BT.

Deposit the iron pipe alongside the iron post.

N. 0° 16' W., beginning new measurement.

Descend 125 ft. over NE. slope.

6.00 Gravelled road, 30 lks. wide, bears N. 25° W. and S. 25° E.

7.40 Ravine, drains E.; asc. 250 ft. over SE. slope.

8.85 Gravelled road, 30 lks. wide, bears N. 50° E. and S. 45° W.

41.14 The closing cor. of Tps. 25 S., Rs. 1 and 2 W., monumented with an iron post, 3 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

T 24 S R 1 W
 S 31

S 1 | S 6
T 25 S
CC
1951

from which the remains of bearing trees mkd. by White and Tallett

A root hole, bears S. 41 1/4° E., 42 lks. dist., with a down sawed fir stump alongside, 28 ins. diam., with scribe marks T25S R1W S6 BT visible on open blaze.

A root hole, bears S. 74 3/4° W., 19 lks. dist., with a down sawed fir stump alongside, 26 ins. diam., with fragmentary scribe marks visible on open blaze.

and bearing trees mkd. by Vernon R. Tracy, Deputy Douglas County Surveyor, in 1967, as described in a Douglas County Surveyor's Record

A fir, 34 ins. diam., bears S. 73° E., 64 lks. dist., with fragmentary scribe marks visible on open blaze.

A cedar, 13 ins. diam., bears S. 70° W., 173 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

and new bearing trees

A hemlock, 13 ins. diam., bears S. 64 1/2° E., 35 lks. dist., mkd. T25S R1W S6 CC BT.

A hemlock, 12 ins. diam., bears S. 28° W., 64 lks. dist., mkd. T25S R2W S1 CC BT.

From this point, a monument established by V. W. Hosford, Registered Land Surveyor, No. 53, in 1950, as described in a Douglas County Surveyor's Record, bears N. 16° 37' W., 0.045 chs. dist., monumented with an iron pipe, 1 in. diam., with a steel cap mkd. T25S R1 R2W S1 S6 CC, from which the remains of bearing trees mkd. by Hosford