

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of N. Bdy.,  
T. 25 S., R. 1 W., Willamette Meridian, Oregon

17356

**CHAINS**

66.00

Ravine, drains SE.; asc. 320 ft. over SE. slope.

79.55

Point for the 120 1/16 sec. cor. of sec. 6 only,  
T. 25 S., R. 1 W., hereinafter described.

Ascend 330 ft. over SE. slope.

82.10

Gravelled road, 30 lks. wide, bears N. 15° W. and  
S. 15° E.

95.00

The closing cor., of secs. 1 and 6, hereinbefore  
described.

Ascend 50 ft. over SE. slope.

98.90

Spur, slopes N. 40° E.; desc. 70 ft. over broken NW.  
slope.

108.97

The SW. cor. of T. 24 S., R. 1 W., monumented with an  
iron post, 3 ins. diam., firmly set, projecting 12 ins.  
above ground, with brass cap mkd.

	T 24 S
	R 1 W
	S 31
T 25 S	R 2 W
	1951

from which the remains of the original bearing trees

A fir, 27 ins. diam., bears N. 64 1/4° E., 67 lks.  
dist., with healed blaze.

A chinquapin snag, 8 ins. diam., bears S. 13 1/4° E.,  
20 lks. dist., with scribe marks 25S R1W S6 BT  
visible on open blaze. (1951 Record, S. 11 1/2° E.)

and a bearing tree mkd. by White and Tallett

A fir, 17 ins. diam., bears N. 18 1/4° E., 41 lks.  
dist., with healed blaze. (Record, N. 17 1/4° E.)

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, maple, oak, chinquapin,  
alder, and madrone; undergrowth, salal, Oregon grape,  
vine maple, poison oak, rhododendron, fern, and grasses.

Dependent Resurvey of  
a Portion of the Subdivisional Lines,  
T. 25 S., R. 1 W., Willamette Meridian, Oregon

(Restoring the survey by Hezekiah H. Johnson in 1900)

From the 1/4 sec. cor. of secs. 6 and 7, perpetuated and  
recorded by Vernon R. Tracy, Deputy Douglas County  
Surveyor, in 1967, monumented with an iron post, 1 1/4 ins.  
diam., firmly set, projecting 8 ins. above ground, with  
brass cap mkd.

County Surveyors Office

	T 25 S
	S 6
1/4	S 7
	R 1 W
	1967