

County Surveyor's Record, Douglas County, Oregon

17357 Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 1 W., Willamette Meridian, Oregon

CHAINS													
	<p>from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A cedar, 30 ins. diam., bears N. 2° W., 33 1/2 lks. dist., with healed blaze. (Record, 35 lks.)</p> <p>and bearing trees mkd. by Tracy</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 26° E., 21 1/2 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A hemlock, 10 ins. diam., bears S. 31° W., 29 lks. dist., with healed blaze.</p> <p>and a tree not of known record</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 37° E., 62 lks. dist., with healed blaze.</p> <p>N. 88° 34' W., bet. secs. 6 and 7.</p> <p>Ascend 295 ft. over SE. slope, through heavy timber and dense undergrowth.</p>												
6.85	Spur, slopes S. 5° E.; desc. 455 ft. over NW. slope.												
15.85	Gravelled road, 20 lks. wide, bears N. 5° W. and S.												
16.60	Surprise Creek, 20 lks. wide, course S. 10° W.; asc. 700 ft. over broken SE. slope.												
43.35	Ridge, bears N. 30° W. and S. 30° E.; desc. 75 ft over SW. slope.												
60.75	Ravel Creek, 8 lks. wide, course S. 60° E.; asc. 395 ft. over NE. slope.												
76.22	<p>Point for the 120 1/16 sec. cor. of secs. 6 and 7.</p> <p>Seat a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in drill hole, with top mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr> <td></td> <td style="text-align: center;">S 6</td> <td></td> </tr> <tr> <td style="text-align: center;">1/16</td> <td style="text-align: center;">—————</td> <td style="text-align: center;">120</td> </tr> <tr> <td></td> <td style="text-align: center;">S 7</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1981</td> <td></td> </tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A hemlock, 15 ins. diam., bears S. 34 3/4° W., 90 lks. dist., mkd. 120 1/16 S7 BT.</p> <p style="padding-left: 40px;">A hemlock, 13 ins. diam., bears N. 11 3/4° W., 48 1/2 lks. dist., mkd. 120 1/16 S6 BT.</p> <p>Ascend 65 ft. over NE. slope.</p>		S 6		1/16	—————	120		S 7			1981	
	S 6												
1/16	—————	120											
	S 7												
	1981												
77.50	Spur, slopes N. 50° E.; asc. 450 ft. over broken NE. slope.												
87.60	Gravelled road, 30 lks. wide, bears N. 30° W. and S. 30° E.												
91.07	The closing cor. of secs. 6 and 7, on the W. bdy. of the Tp., reestablished at proportionate dist. and recorded by V. W. Hosford, Registered Land Surveyor, No. 253, in 1950, and accepted as the best available evidence of the position of the original cor., monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 4 ins. above ground, from which bearing trees mkd. by Hosford												