

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 1 W., Willamette Meridian, Oregon

17360

CHAINS

T 24 S R 1 W

1/4 S 6
T 25 S R 1 W
1981

from which

A fir, 16 ins. diam., bears S. 33 1/2° E., 48 lks.
dist., mkd. 1/4 S6 BT.

A fir, 6 ins. diam., bears S. 47 1/2° W., 51 lks.
dist., mkd. X BT.

From this point, the 1/4 sec. cor. of sec. 31, T. 24 S.,
R. 1 W., bears N. 89° 39' W., 0.47 chs. dist., hereinbe-
fore described.

The point for the 120 1/16 sec. cor. of sec. 6 only,
T. 25 S., R. 1 W., is at proportionate dist. on the
N. bdy. of sec. 6.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in
the ground, with brass cap mkd.

120 1/16 S 6

1981

from which

A fir, 5 ins. diam., bears S. 81° E., 15 lks.
dist., mkd. 120 1/16 S6 BT.

A fir, 5 ins. diam., bears S. 51° W., 24 lks.
dist., mkd. 120 1/16 S6 BT.

Subdivision of Section 6,
T. 25 S., R. 1 W., Willamette Meridian, Oregon

From the 1/4 sec. cor. of secs. 6 and 7.

N. 2° 44' E., on the N. and S. center line of sec. 6,
marking and blazing the true line.

Ascend 960 ft. over broken SE. slope, through heavy
timber and dense undergrowth.

29.70 Spur, slopes S. 25° W.; asc. 40 ft. over SW. slope.

30.85 Spur, slopes N. 85° W.; desc. 95 ft. over NW. slope.

36.75 Ravine, drains W.; asc. 130 ft. over SW. slope.

41.55 Spur, slopes N. 70° W.; desc. 40 ft. over broken NW.
slope.

42.53 Point for the center 1/4 sec. cor. of sec. 6, at intersec-
tion with the E. and W. center line.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in
the ground, with brass cap mkd.

T 25 S R 1 W
C 1/4 S 6
1981