

County Surveyor's Record, Douglas County, Oregon

17361

Subdivision of Section 6,
T. 25 S., R. 1 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears N. 66 1/2° E., 27 1/2 lks. dist., mkd. C 1/4 S6 BT.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 37 1/2° W., 23 lks. dist., mkd. C 1/4 S6 BT.</p> <p>Descend 285 ft. over broken NW. slope.</p>
49.75	Dirt road, 15 lks. wide, bears N. 80° E. and S. 80° W.
50.55	Ravine, drains N. 60° W.; asc. 195 ft. over broken SW. slope.
52.15	Dirt road, 15 lks. wide, bears N. 40° W. and S. 50° E.
57.45	Spur, slopes N. 70° W.; desc. 310 ft. over NW. slope.
63.95	Dirt road, 15 lks. wide, bears E. and W.
67.30	Ravine, drains N. 65° W.; asc. 210 ft. over SW. slope.
75.30	Spur, slopes W.; desc. 280 ft. over NW. slope.
82.25	Ravine, drains W.; asc. 60 ft. over SW. slope.
84.37	The 1/4 sec. cor. of sec. 6 only, on the N. bdy. of the Tp.
	<p>From the 1/4 sec. cor. of secs. 5 and 6.</p> <p>N. 89° 43' W., on the E. and W. center line of sec. 6.</p> <p>Ascend 60 ft. over NE. slope, through clear-cut area and dense undergrowth.</p>
2.40	Spur, slopes N. 40° E.; desc. 20 ft. over NW. slope.
4.00	Creek, 3 lks. wide, course N. 25° E.; asc. 200 ft. over SE slope.
9.95	Spur, slopes S. 70° E.; asc. 235 ft. over broken E. slope.
24.50	Ridge, bears N. 20° E. and S. 5° W.; desc. 335 ft. over NW. slope.
39.81	The center 1/4 sec. cor. of sec. 6.
	Descend 675 ft. over broken NW. slope.
59.30	Dirt road, 15 lks. wide, bears N. and S.
74.50	Surprise Creek, 25 lks. wide, course S. 25° E.; asc. 475 ft. over broken SE. slope.
98.40	Creek, 8 lks. wide, course S. 20° E.; asc. 200 ft. over SE. slope.
115.10	Creek, 4 lks. wide, course S. 60° E.; asc. 260 ft. over NE. slope.
117.93	Point for the center 120 1/16 sec. cor. of sec. 6.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.