

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 6,
T. 25 S., R. 1 W., Willamette Meridian, Oregon

17362

CHAINS	
	$C \frac{1/16}{S 6} 120$ 1981
	from which A fir, 5 ins. diam., bears S. 51 1/2° W., 21 lks. dist., mkd. C 120 1/16 S6 BT. A fir, 8 ins. diam., bears N. 6° W., 38 lks. dist., mkd. C 120 1/16 S6 BT. Corner falls in ravine, drains N. 80° E. Ascend 590 ft. over broken SE. slope.
129.60	Gravelled road, 30 lks. wide, bears N. and S.
133.08	The 1/4 sec. cor. of sec. 6 only, on the W. bdy. of the Tp.
<p>From the 120 1/16 sec. cor. of secs. 6 and 7. N. 0° 13' E., on the N. and S. 120 1/16 line of the SW 1/4 of sec. 6. Descend 235 ft. over NE. slope, through dense under- growth.</p>	
5.70	Creek, 6 lks. wide, course S. 75° E.; asc. 515 ft. over SE. slope.
20.80	Spur, slopes S. 85° E.; desc. 315 ft. over NE. slope.
27.55	Creek, 2 lks. wide, course N. 45° E.; asc. 115 ft. over SE. slope.
34.15	Spur, slopes S. 60° E.; desc. 170 ft. over NE. slope.
40.95	The center 120 1/16 sec. cor. of sec. 6.
<p>From the center 120 1/16 sec. cor. of Sec. 6. N. 0°10' E., on the N. & S. 120 1/16 line of the NW 1/4 Sec. 6. Ascend 45 ft. over broken SE. slope, through scattering timber and dense undergrowth.</p>	
1.35	Spur, slopes E.; desc. 60 ft. over NE. slope.
3.95	Creek, 3 lks. wide, course S. 50° E.; asc. 200 ft. over SE. slope.
9.95	Spur, slopes S. 70° E.; desc. 100 ft. over NE. slope.
14.55	Creek, 2 lks. wide, course E.; asc. 20 ft. over SE. slope.
15.60	Spur, slopes S. 60° E.; desc. 20 ft. over NE. slope.
16.65	Creek, 2 lks. wide, course S. 55° E.; asc. 160 ft. over SE. slope.
21.40	Spur, slopes S. 70° E.; desc. 65 ft. over broken N. slope.