

# County Surveyor's Record, Douglas County, Oregon

17365

T. 30 S., R. 5 W., Willamette Meridian, Oregon

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and subdivision of section 29, Township 30 South, Range 5 West, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

The north, south, and west boundaries of the township and a portion of the subdivisional lines were surveyed by Nathaniel Ford, U.S. Deputy Surveyor, in 1854.

The boundaries of Donation Land Claim Nos. 44 and 46 were surveyed by Josiah A. Burnett and Elliott N. Bowman, U.S. Deputy Surveyors, in 1855.

The corner of sections 28, 29, 32, and 33 was remonumented without survey by Lynn M. Roseberry, Cadastral Surveyor, in 1967.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 1069, Oregon, dated June 15, 1981.

The directions of the lines were determined by deflections from azimuths obtained by direct solar observations and refer to the true meridian.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein. All lines not forming closures were measured twice. Only the lines bounding or crossing public lands were blazed.

The geographic position of the corner of sections 29, 30, 31, and 32 as determined by a Horizontal Control Survey by the Douglas County Surveyors Office in 1979, is as follows:

Latitude 42° 55' 37.0" N. Longitude 123° 19' 27.1" W.

The mean magnetic declination is 19° 45' E.

Dependent Resurvey of  
a Portion of the Subdivisional Lines,  
T. 30 S., R. 5 W., Willamette Meridian, Oregon

(Restoring the survey by Nathaniel Ford in 1854)

Beginning at the cor. of secs. 28, 29, 32, and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.

T 30 S	R 5 W
S 29	S 28
S 32	S 33
1967	