

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **17366**
T. 30 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

from which the remains of the original bearing trees

A sawed black oak stump, 28 ins. diam., bears
N. 86° E., 13 lks. dist., no marks visible.

A white oak, 35 ins. diam., bears S. 58° W.,
76 lks. dist., with healed blaze.

and a bearing tree mkd. by John H. Markham, Jr.,
Registered Engineer, No. 2880, in 1949

A white oak, 20 ins. diam., bears N. 67 1/2° W.,
165 lks. dist., with healed blaze.

and the remains of a bearing tree mkd. by James W. Byron,
Deputy County Surveyor, in 1963

A sawed white oak stump, 9 ins. diam., bears
S. 3 1/4° E., 17 lks. dist., with scribe marks
CS BT visible on open blaze.

and bearing trees mkd. by R. B. Kimberling and Stephen
Flause, Deputy County Surveyors, in 1978

A fir, 11 ins. diam., bears N. 1 1/2° E., 109 lks.
dist., with scribe marks T30S R5W S32 CS BT
visible on open double blaze.

An oak, 8 ins. diam., bears S. 1° W., 28 1/2 lks.
dist., with scribe marks T30S R5W S32 CS BT
visible on open double blaze.

N. 1° 02' E., bet. secs. 28 and 29, marking and blazing
the true line.

Ascend 20 ft. over SE. slope, through heavy timber and
dense undergrowth.

1.90 Spur, slopes N. 80° E.; desc. 20 ft. over NE. slope.

3.25 Ravine, drains S. 80° E.; asc. 5 ft. over SE. slope.

4.00 Spur, slopes S. 85° E.; desc. 5 ft. over NE. slope.

5.00 Ravine, drains S. 75° E.; asc. 385 ft. over SE. slope.

7.45 Gravelled road, 20 lks. wide, bears N. 80° W. and S. 75° E.

19.00 Point for the S 1/16 sec. cor. of secs. 28 and 29.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with aluminum cap mkd.

S 1/16
S 29 | S 28
1981

from which

A fir, 14 ins. diam., bears N. 25 1/2° E., 89 lks.
dist., mkd. S 1/16 S28 BT.

A twin madrone, 27 ins. diam., bears N. 20° W.,
29 1/2 lks. dist., mkd. S 1/16 S29 BT on bark.

Ascend 170 ft. over SE. slope.