

County Surveyor's Record, Douglas County, Oregon

17367

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 5 W., Willamette Mer., Oregon

CHAINS

28.50

Ridge, bears N. 55° E., and S. 55° W.; desc. 360 ft. over broken NE. slope, changing to NW.

38.00

The 1/4 sec. cor. of secs. 28 and 29, perpetuated and recorded by John H. Markham, Jr., Registered Engineer, No. 2880, in 1951, from original evidence no longer in existence, subsequently perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 16 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S
1/4 S 29 | S 28
R 5 W
1963

from which the remains of a bearing tree mkd. by Markham

A root hole, bears N. 13° E., 7 1/2 lks. dist., with a downed fir alongside, 24 ins. diam., no marks visible.

and bearing trees mkd. by Byron

A fir, 24 ins. diam., bears S. 73° E., 62 lks. dist., with healed double blaze.

A fir, 26 ins. diam., bears S. 28 1/2° W., 20 lks. dist., with healed double blaze.

Land, mountainous.

Soil, rocky clay.

Timber, oak, fir, cedar, madrone, chinquapin, maple, pine, and alder; undergrowth, poison oak, arrowwood, hazel, fern, Oregon grape, huckleberry, salmonberry, blackberry, vine maple, and young timber.

From the 1/4 sec. cor. of secs. 29 and 32, perpetuated and recorded by Larry E. Monrean, Deputy County Surveyor, in 1979, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.

DOUGLAS COUNTY SURVEYOR

T 30 S R 5 W
1/4 S 29
S 32
1979

from which the remains of an original bearing tree

A sawed fir stump, 35 ins. diam., bears N. 60° W., 86 lks. dist., no marks visible.
(Record, 84 lks.)

and bearing trees mkd. by Monrean

A madrone, 10 ins. diam., bears S. 68° W., 44 lks. dist., with scribe marks 1/4 S32 CS BT visible on open double blaze.